Review of Preconditioning for the Compressible Fluid Dynamic Equations

E. Turkel
School of Mathematical Sciences
Sackler Faculty of Exact Sciences
Tel-Aviv University
Tel-Aviv, Israel

1 Introduction

Over the past years several preconditioning methods have appeared with the aim to solve nearly incompressible flow problems with numerical algorithms designed for the compressible flows. The developments are motivated by several observations. First, there exist flow problems of mixed compressible/incompressible type. That is, part of the flow region is incompressible with locally low Mach numbers, whereas significant compressibility effects occur in other regions of the flow. A typical example in aerodynamics is the flow over a wing at a high angle of attack. Other examples include duct flow where the flow in most of the region is highly subsonic but sharp changes in the geometry of the duct cause the flow to become supersonic in a portion of the region. Moreover, low speed flows may be compressible, because of surface heat transfer or volumetric heat addition. Finally, engineers prefer to use existing compressible flow codes over the broadest range of flow conditions possible in order to avoid dealing with multiple flow codes.

The difficulty in solving the compressible equations for low Mach numbers are associated with the large disparity of the acoustic wave speed, $u + a$, and the waves convected at the fluid speed, u. The application of preconditioning changes the eigenvalues of the system of compressible flow equations in order to remove this large disparity of wave speeds. For example, the time derivatives are premultiplied by a matrix which slows the speed of the acoustic waves down towards the fluid speed. A review of preconditioning methods for convection dominated flow problems has been published by Turkel [25]. Successful applications to low Reynolds number viscous flows are reported by Choi and Merkle [5].

There are two basic views of preconditioning methods. The first, which arose in applications to elliptic equations, views preconditioning as a way to accelerate the convergence of the iterative method. This is usually done on the matrix level. Thus, once convergence is achieved the solution should be identical to the original solution. The second approach, which we advocate for low speed flow is to view preconditioning as changing the differential equations to be solved. Thus, as a consequence of preconditioning the basic scheme can be changed, e.g. the artificial viscosity or upwinding. Similarly, the boundary conditions satisfied are based on the preconditioned equations rather than the physical equations. The justification for this is presented in [27] is that the "standard" numerical schemes for the compressible equations do not converge to a scheme for the incompressible equations (using a pseudo-compressibility approach) as the Mach number goes to zero. However, a proper preconditioning leads to a numerical scheme that does behave appropriately for low Mach numbers.

We present a generalization of the preconditioners given by Turkel [25, 26], Choi-Merkle [5] and van Leer et. al [30]. The characteristic variables needed to compute flow conditions at inflow or outflow boundaries are also derived. The accuracy of numerical solutions of the preconditioned flow equations is also investigated. We discuss nonconservative and conservative artificial dissipation models and the effects of the preconditioning matrix upon accuracy. The influence of dissipation coefficients and the choice of preconditioning matrix upon grid convergence of the numerical solutions are investigated. Applications to two and three dimensional inviscid and viscous flows are presented.

We demonstrate that preconditioning can be combined with well-known convergence acceleration techniques such as residual smoothing and multigrid. Indeed, it is no surprise that the clustering of eigenvalues with preconditioning improves the damping of transient high-frequency modes to an extent, that efficient multigrid computations of flows with very low Mach numbers are now possible.

1.1 General requirements

For both the incompressible and compressible equations we consider systems of the form

$$w_t + f_x + g_y = 0.$$

This system is written in conservation form though for some applications this is not necessary. Our analysis will be based on the linearized equations so that the conservation form does not appear in the analysis though it does appear in the final numerical approximation. This system is now replaced by

$$\mathbf{P}^{-1} w_t + f_x + g_y = 0,$$

or in linearized form

$$\mathbf{P}^{-1} w_t + A w_x + B w_y = 0, \tag{1.1}$$

with A and B constant matrices.

In order for this system to be equivalent to the original system, in the steady state, we demand that $\mathbf{P}^{-1}$ have an inverse. This only need be true in the flow regime under consideration. We shall see later that frequently $\mathbf{P}$ is singular at stagnation points and also along sonic lines. Thus, we will consider strictly subsonic flow without a stagnation point. For transonic flow it is necessary to smooth out the singularity in a neighborhood of the sonic line. We also assume that the Jacobian matrices $A = \frac{\partial f}{\partial w}$ and $B = \frac{\partial g}{\partial w}$ are simultaneously symmetrizable. In terms of the 'symmetrizing' variables we also demand that $\mathbf{P}$ be positive definite.

Assuming the steady state has a unique solution, it does not matter which system we march to a steady state. We shall later see that for the finite difference approximations the steady state solutions are not necessarily the same and usually the preconditioned system leads to a better behaved steady state.

2 Incompressible Equations

We first consider the incompressible inviscid equations in primitive variables.

$$\begin{aligned} u_x + v_y &= 0 \\ u_t + u u_x + v u_y + p_x &= 0 \\ v_t + u v_x + v v_y + p_y &= 0 \end{aligned}$$

We consider generalizations of Chorin's pseudo-compressibility method [6]. Using the preconditioning suggested in [25] (with $\alpha = 1$) we have

$$\begin{aligned} \frac{1}{\beta^2} p_t + u_x + v_y &= 0 \\ \frac{u}{\beta^2} p_t + u_t + u u_x + v u_y + p_x &= 0 \\ \frac{v}{\beta^2} p_t + v_t + u v_x + v v_y + p_y &= 0 \end{aligned} \tag{2.1}$$

We can also write this in matrix form using

$$\mathbf{P}^{-1} = \begin{pmatrix} 1/\beta^2 & 0 & 0 \\ u/\beta^2 & 1 & 0 \\ v/\beta^2 & 0 & 1 \end{pmatrix}, \mathbf{P} = \begin{pmatrix} \beta^2 & 0 & 0 \\ -u & 1 & 0 \\ -v & 0 & 1 \end{pmatrix}$$

Multiplying by $\mathbf{P}$ we rewrite this as

$$w_t + \mathbf{P} A w_x + \mathbf{P} B w_y = 0.$$

We also define

$$D = \omega_1 A + \omega_2 B \quad -1 \le \omega_1, \omega_2 \le 1$$

where ω_1, ω_2 are the Fourier transform variables in the x and y directions respectively. The speeds of the waves are now given by the roots of $det(\lambda I - \mathbf{P} A \omega_1 - \mathbf{P} B \omega_2) = 0$. Let $q = u\omega_1 + v\omega_2$. Then the eigenvalues of $\mathbf{P}$D are

$$d_0 = q \quad , \quad d_\pm = \pm\beta \tag{2.2}$$

and so the 'acoustic' speed is isotropic.

The spatial derivatives involve symmetric matrices, i.e. D is a symmetric matrix but $\mathbf{P}$ is not symmetric. Thus, while the original system was symmetric hyperbolic the preconditioned system is no longer symmetric. In [25] it is shown that as long as

$$\beta^2 > (u^2 + v^2)$$

then the equations can be symmetrized. On the other hand the eigenvalues are most equalized if $\beta^2 = (u^2 + v^2)$ [25]. Hence, we wish to choose β^2 slightly larger than $u^2 + v^2$. However, numerous calculations verify, that in general, a constant β is the best for the convergence rate.

We wish to stress that β has the dimensions of a speed. Therefore, β cannot be a universal constant. There are papers that claim that $\beta = 1$ or $\beta = 2.5$ are optimal. Such claims cannot be true in general. It is simple to see that if one nondimensionalizes the equation then β gets divided by a reference velocity. Hence, the optimal 'constant' β depends on the dimensionalization of the problem and in particular depends on the inflow conditions. In many calculations the inflow mass flux is equal to 1 or else $p+(u^2+v^2)/2=1$. Such conditions will give an optimal β close to one. However, if one chooses the incoming mass flux as ten then the optimal β will be larger.

We next define the Bernoulli function

$$H = p + (u^2+v^2)/2.$$

Bernoulli's theorem states that for steady inviscid flow H is constant along streamlines. We now multiply the second equation of (2.1) by u and the third equation of (2.1) by v and add these two equations. If $\beta^2 = u^2+v^2$, the result is

$$H_t + uH_x + vH_y = 0. \tag{2.3}$$

Thus, by altering the time dependence of the equations we have constructed a new equation in which H is convected along streamlines. Furthermore, if H is a uniform constant both initially and at inflow then H will remain constant for all time. On the numerical level this will usually not be true because of the introduction of an artificial viscosity or because of upwinding. For viscous flow, (2.3) is replaced by

$$H_t + uH_x + vH_y = \frac{1}{Re}(u\Delta u + v\Delta v)$$

We note that these relationships for H follow from the momentum equations and do not depend on the form of the continuity equation. Hence, we consider the following generalization of (2.1)

$$\begin{aligned}
\frac{1}{\beta^2}p_t + aH_t + u_x + v_y &= 0\\
\frac{\alpha u}{\beta^2}p_t + u_t + uu_x + vu_y + p_x &= 0\\
\frac{\alpha v}{\beta^2}p_t + v_t + uv_x + vv_y + p_y &= 0
\end{aligned}$$

where, a is a free parameter. The eigenvalues of $\mathbf{P}$D are independent of the parameter a and are given by (2.2). For $a=0, \alpha=1$ we recover our original scheme. For $a=-1$ the time derivative of the pressure no longer appears in the continuity equation. For general β we have

$$\mathbf{P}^{-1} = \frac{1}{\beta^2}\begin{pmatrix} (a+1) & au & av \\ \alpha u & \beta^2 & 0 \\ \alpha v & 0 & \beta^2 \end{pmatrix},$$

$$\mathbf{P} = \frac{1}{d}\begin{pmatrix} \beta^2 & -au & -av \\ -\alpha u & 1+a-\frac{a\alpha v^2}{\beta^2} & \frac{a\alpha uv}{\beta^2} \\ -\alpha v & \frac{a\alpha uv}{\beta^2} & 1+a-\frac{a\alpha u^2}{\beta^2} \end{pmatrix}$$

where $d = 1+a-a\alpha\frac{u^2+v^2}{\beta^2}$ and we require that $d \geq 0$. If $\beta^2 = u^2+v^2$ and $\alpha = 1$ then

$$\mathbf{P} = \begin{pmatrix} u^2+v^2 & -au & -av \\ -u & 1+\frac{au^2}{u^2+v^2} & \frac{auv}{u^2+v^2} \\ -v & \frac{auv}{u^2+v^2} & 1+\frac{av^2}{u^2+v^2} \end{pmatrix}$$

In [26] an analogy to the symmetric preconditioning of van Leer, Lee and Roe was constructed for the incompressible equations. If we choose $a=1, \alpha=1$ we get this preconditioning of van Leer et. al., i.e. $\mathbf{P}$ is symmetric.

These examples show that the preconditioning is not unique. If fact, since the determinant of the transpose of a matrix is equal to the determinant of the original matrix it follows that the transpose of $\mathbf{P}$ is also a preconditioner with the same eigenvalues for the preconditioned system. In general, these various systems will have similar eigenvalues but different eigenvectors for the preconditioned system. Calculations show that the system given by $\mathbf{P}$ in (2.1) is more robust and converges faster than that with the transpose preconditioner. This shows that it is not sufficient to consider just the eigenvalues but that the eigenvectors are also of importance. However, even when $\mathbf{P}$ is symmetric $\mathbf{P}D$ is not symmetric and so the eigenvectors of the preconditioned system do not form an orthogonal basis.

We next examine some general form that the preconditioner can have. For this analysis it is easier to use streamwise coordinates as suggested in [30] and so $v=0$. Let u_* be some normalization of the velocity components, then

$$A = \begin{pmatrix} 0 & u_* & 0 \\ u_* & u & 0 \\ 0 & 0 & u \end{pmatrix}, \quad B = \begin{pmatrix} 0 & 0 & u_* \\ 0 & 0 & 0 \\ u_* & 0 & 0 \end{pmatrix}$$

Then the "convective" eigenvector for the non-preconditioned system is

$$\begin{pmatrix} 0 \\ \omega_2 \\ -\omega_1 \end{pmatrix}.$$

The "acoustic" eigenvectors are given by

$$\left(\begin{array}{c}\frac{-u\omega_1+\sqrt{(u\omega_1)^2+4u_*^2}}{2}\\ u_*\omega_1\\ u_*\omega_2\end{array}\right),\left(\begin{array}{c}\frac{-u\omega_1-\sqrt{(u\omega_1)^2+4u_*^2}}{2}\\ u_*\omega_1\\ u_*\omega_2\end{array}\right)$$

We now consider preconditioners of the form

$$\mathbf{P}=\left(\begin{array}{ccc} a & b & 0\\ c & d & 0\\ 0 & 0 & 1\end{array}\right). \tag{2.4}$$

We want the eigenvalues of $\mathbf{P}D$ to be $\omega_1 u$, $\pm u$. This gives us three relations for the four unknowns:

$$\begin{aligned} a &= \frac{u^2}{u_*^2}\\ (b+c)u_* + du &= 0\\ u^2 d - bcu_*^2 &= u^2 \end{aligned}$$

The values suggested in [25] are $b=0, c=-\frac{u}{u_*}, d=1$ while the values suggested in [30] are $b=c=-\frac{u}{u_*}, d=2$. We next present the eigenvectors of $\mathbf{P}D$ in terms of the elements of $\mathbf{P}$. We exclude the case $\omega_2=0, \omega_1=\pm 1$ as in this case $\mathbf{P}D$ has a double eigenvalue u and the eigensystem completely changes. Then the "convective" eigenvector is

$$\left(\begin{array}{c} 0\\ \omega_2\\ -(1+b\frac{u_*}{u})\omega_1\end{array}\right).$$

The "acoustic" eigenvectors are given by

$$\left(\begin{array}{c} \frac{u^2}{u_*}-bu\omega_1^2-\frac{u^2\omega_1}{u_*}+bu\omega_1\\ u_*(a+b\omega_1^2)-u_*(b+c)\omega_1\\ (u_*b\omega_1+u)\omega_2\end{array}\right),$$

$$\left(\begin{array}{c} \frac{u^2}{u_*}-bu\omega_1^2+\frac{u^2\omega_1}{u_*}-bu\omega_1\\ u_*(a+b\omega_1^2)+u_*(b+c)\omega_1\\ (u_*b\omega_1-u)\omega_2\end{array}\right).$$

We note that the convective eigenvector is the same as before the preconditioning for the choice $b=0$. The two acoustic eigenvectors are orthogonal to each other if we choose $b=0$ and $c^2=\frac{u^2(1-\frac{u^2}{u_*^2})}{u_*^2}$. This is similar, but not identical, to the choice suggested in [25]. There is no way to make the convective eigenvector normal to both acoustic eigenvectors for preconditioners of the form (2.4).

3 Algorithm I

We consider the preconditioned Euler equation written as

$$P^{-1}w_t + Aw_x + Bw_y = 0 \tag{3.1}$$

The form of the matrices A, B depend on the choice of the variables w . We shall first consider the variables $w=w_0=(p,u,v,S)$ with $dS=dp-a^2 d\rho$. We then have

$$A_0=\left(\begin{array}{cccc} u & \rho a^2 & 0 & 0\\ \frac{1}{\rho} & u & 0 & 0\\ 0 & 0 & u & 0\\ 0 & 0 & 0 & u\end{array}\right)\quad B_0=\left(\begin{array}{cccc} v & 0 & \rho a^2 & 0\\ 0 & v & 0 & 0\\ \frac{1}{\rho} & 0 & v & 0\\ 0 & 0 & 0 & v\end{array}\right)$$

The preconditioners we shall consider contain a free parameter β. Unfortunately, the papers that have dealt with this subject all use different definitions of this free variable. Thus, for Choi and Merkle $\beta\sim a^2$ while for Turkel $\beta^2\sim u^2+v^2$ (based on Chorin's work on pseudo-compressibility) while for van Leer $\beta=\sqrt{1-M^2}$ (based on fluid dynamic notation). In this paper we shall concentrate on the Choi-Merkle and Turkel preconditioners. To avoid confusion we shall use the Choi-Merkle choice for β within this paper. In terms of these variables we consider the following preconditioner which is a generalization of previous preconditioners. For $\delta=0$ we recover the preconditioner suggested by Turkel [25, 26] while for $\delta=1, \alpha=0$ we recover the preconditioner suggested by Choi and Merkle [5]. Note that δ is a new free parameter to generalize the Choi-Merkle and Turkel preconditioners. It does not correspond to the δ in the Choi-Merkle paper.

$$\begin{aligned} P_0^{-1} &= \left(\begin{array}{cccc} \frac{a^2}{\beta M_r^2} & 0 & 0 & \delta\\ \frac{\alpha u}{\rho\beta M_r^2} & 1 & 0 & 0\\ \frac{\alpha v}{\rho\beta M_r^2} & 0 & 1 & 0\\ 0 & 0 & 0 & 1\end{array}\right) \qquad (3.2)\\ P_0 &= \left(\begin{array}{cccc} \frac{\beta M_r^2}{a^2} & 0 & 0 & -\frac{\beta M_r^2}{a^2}\delta\\ -\frac{\alpha u}{\rho a^2} & 1 & 0 & \frac{\alpha u}{\rho a^2}\delta\\ -\frac{\alpha v}{\rho a^2} & 0 & 1 & \frac{\alpha v}{\rho a^2}\delta\\ 0 & 0 & 0 & 1\end{array}\right) \end{aligned}$$

The guiding principle is that near stagnation points βM_r^2 should not be allowed to approach zero. We also desire that for supersonic flow that preconditioner be turned off, i.e. $\beta M_r^2=a^2$, $\alpha=0$, $\delta=0$. We choose

$$\begin{aligned} \beta M_r^2 &= K_2(u^2+v^2) \qquad (3.3)\\ K_2 &= K_1\left(1+\frac{(1-K_1M_0^2)}{K_1M_0^4}M^2\right) \end{aligned}$$

In addition we make sure that βM_r^2 is never greater than a^2.

This returns βM_r^2 to its non-preconditioned value at M_0. K_1 typically varies between 1.0 and 1.1. $K-1$ also depends on α [25] and may depend on the local cell Reynolds number [5]. Thus,

$$P_0 A_0 = \begin{pmatrix} \frac{\beta M_r^2 u}{a^2} & \rho\beta M_r^2 & 0 & \frac{-\beta M_r^2 u\delta}{a^2} \\ \frac{1-\frac{\alpha u^2}{a^2}}{\rho} & (1-\alpha)u & 0 & \frac{\alpha u^2\delta}{\rho a^2} \\ \frac{-\alpha uv}{\rho a^2} & -\alpha v & u & \frac{\alpha uv\delta}{\rho a^2} \\ 0 & 0 & 0 & u \end{pmatrix}$$

The eigenvalues of $P_0 A_0$ are

$$\begin{aligned} \lambda_0 &= u \qquad (3.4) \\ \lambda_\pm &= 0.5\left(zu \pm \sqrt{z^2u^2 + 4\beta M_r^2(1-\frac{u^2}{a^2})}\right) \end{aligned}$$

$z = 1-\alpha+\frac{\beta M_r^2}{a^2}$. In particular if $\alpha = 1+\frac{\beta M_r^2}{a^2}$ then $z=0$ and $\lambda_\pm = \pm\sqrt{\beta M_r^2(1-M^2)}$. The right eigenvectors are given by the columns of

$$R^{-1} = \begin{pmatrix} \rho\beta M_r^2 & \rho\beta M_r^2 & 0 & 0 \\ \lambda_+ - \frac{\beta M_r^2}{a^2}u & \lambda_- - \frac{\beta M_r^2}{a^2}u & 0 & \frac{\delta u}{\rho a^2} \\ \frac{\alpha v\lambda_+}{u-\lambda_+} & \frac{\alpha v\lambda_-}{u-\lambda_-} & 1 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

We note that for $\delta = 0$ and $\alpha = 0$ the two eigenvectors for the convective speeds are orthogonal to each other and to the acoustic eigenvectors. Of course, orthogonality of eigenvectors depends on the basis chosen, i.e. on the variables used in constructing P_0 and A_0. Furthermore, as the Mach number goes to zero the determiant of R^{-1} depends only on βM_r^2. Thus, the condition number of the transformation is well behaved as long as βM_r^2 is bounded away from zero as the Mach number approaches zero.

For generalized coordinates replace this by

$$\begin{aligned} U &= us_x + vs_y \quad |S_\xi|^2 = s_x^2 + s_y^2 \qquad (3.5) \\ \lambda_\pm &= \frac{zU \pm \sqrt{z^2U^2 + 4\beta M_r^2(|S_I|^2 - \frac{U^2}{a^2})}}{2} \end{aligned}$$

where $S_\xi = (s_x, s_y)$ is the cell face vector in ξ-direction. The largest eigenvalue is then used to determine the (inviscid) time step. We note that these eigenvalues are independent of δ. For M ~ 0, $\lambda_\pm \sim 0.5u\left((1-\alpha) \pm \sqrt{(1-\alpha)^2+4}\right)$. So for $\alpha = 0$ the condition number is $\frac{1+\sqrt{5}}{1-\sqrt{5}} \sim 2.6$ while for $\alpha = 1$ the condition number is $1+O(M)$. If we choose $\alpha = 1+\frac{\beta M_r^2}{a^2}$ and $\beta M_r^2 = \frac{M^2c^2}{1-M^2}$ then we get the same eigenvalues as those of the symmetric optimal preconditioner to be presented in the next section (see 5.1). For small Mach numbers this is similar to what we obtained with $\alpha = 1$ while at the sonic line α and β become infinite which reduces the condition number of the preconditioned system near the sonic line. We shall also express these matrices in terms of the variables $w_4 = (p, u, v, T)$. Let

$$g = 1 + (\gamma-1)\delta = \begin{cases} 1, & \text{if } \delta = 0 \\ \gamma, & \text{if } \delta = 1 \end{cases}$$

Then,

$$A_4 = \begin{pmatrix} u & \rho a^2 & 0 & 0 \\ \frac{1}{\rho} & u & 0 & 0 \\ 0 & 0 & u & 0 \\ 0 & (\gamma-1)T & 0 & u \end{pmatrix}$$

$$B_4 = \begin{pmatrix} v & 0 & \rho a^2 & 0 \\ 0 & v & 0 & 0 \\ \frac{1}{\rho} & 0 & v & 0 \\ 0 & 0 & (\gamma-1)T & v \end{pmatrix}$$

Let $m^2 = \frac{\beta M^2}{a^2}$, then

$$P_4^{-1} = \begin{pmatrix} \frac{1}{m^2} - (\gamma-1)\delta & 0 & 0 & \frac{\gamma p}{T}\delta \\ \frac{\alpha u}{\rho\beta M^2} & 1 & 0 & 0 \\ \frac{\alpha v}{\rho\beta M^2} & 0 & 1 & 0 \\ \frac{1}{\rho c_p}\left(\frac{1}{m^2} - g\right) & 0 & 0 & g \end{pmatrix},$$

$$P_4 = \begin{pmatrix} m^2 g & 0 & 0 & -m^2\frac{\gamma p}{T}\delta \\ -\frac{\alpha ug}{\rho a^2} & 1 & 0 & \frac{\alpha u}{\rho a^2}\frac{\gamma p}{T}\delta \\ -\frac{\alpha vg}{\rho a^2} & 0 & 1 & \frac{\alpha v}{\rho a^2}\frac{\gamma p}{T}\delta \\ \frac{1}{\rho c_p}(m^2 g - 1) & 0 & 0 & 1-(\gamma-1)m^2\delta \end{pmatrix}$$

The matrix presented in (3.2) while improving the condition in the neighborhood of $M = 0$ does not improve the condition number in the neighborhood of the sonic line. Indeed in (3.3) we explicitly removed the preconditioning as $M \to 1$. An alternative is to generalize (3.2) so that it is basically the same for low Mach numbers but reduces the condition number near the sonic line.

4 Algorithm II

In [7, 27] an alternate way of preconditioning the fluid dynamics system was introduced. In this approach we do not update the conservation variables, rather we update the variables

$$W = \begin{pmatrix} p' \\ \rho u \\ \rho v \\ E' \end{pmatrix}, \quad F = \begin{pmatrix} \rho u \\ \rho u^2 + p' \\ \rho uv \\ \rho H'u \end{pmatrix},$$

$$G = \begin{pmatrix} \rho v \\ \rho uv \\ \rho v^2 + p' \\ \rho H'v \end{pmatrix}, \quad Q = \begin{pmatrix} p' \\ \rho u \\ \rho v \\ H' \end{pmatrix}$$

$$\frac{\partial W}{\partial t} = \mathbf{P}\left[\frac{\partial F}{\partial x} + \frac{\partial G}{\partial y}\right]$$

where $p' = p - p_\infty$, $E' = c_p\rho(T - T_\infty) - (p - p_\infty) + \frac{\rho(u^2+v^2)}{2} = E + p_\infty - \frac{\gamma p_\infty}{(\gamma-1)\rho_\infty}\rho$ and $\rho H' = E' + p'$. Then

$$\mathbf{P} = \mathbf{I} + \Delta \cdot \begin{bmatrix} 1 - \frac{1}{\Delta} & -\frac{u}{G+h_\infty} & -\frac{v}{G+h_\infty} & \frac{1}{G+h_\infty} \\ -B_2 & \frac{uB_2}{G+h_\infty} & \frac{vB_2}{G+h_\infty} & -\frac{B_2}{G+h_\infty} \\ -B_3 & \frac{uB_3}{G+h_\infty} & \frac{vB_3}{G+h_\infty} & -\frac{B_3}{G+h_\infty} \\ -B_4 & \frac{uB_4}{G+h_\infty} & \frac{vB_4}{G+h_\infty} & -\frac{B_4}{G+h_\infty} \end{bmatrix}$$

$$\begin{aligned} B_1 &= \frac{1}{\beta M_r^2} - \frac{1}{(\gamma-1)h} \\ B_2 &= (B_1 + \frac{\alpha}{\beta M_r^2})u \\ B_3 &= (B_1 + \frac{\alpha}{\beta M_r^2})v \\ B_4 &= B_1 H' + \frac{\alpha(u^2+v^2)}{\beta M_r^2} \end{aligned}$$

where βM_r^2 was previously defined and $h = c_p T$, $G = \frac{u^2+v^2}{2}$, $\Delta = \frac{(G+h_\infty)\beta M_r^2}{h}$ and $\alpha = 1$.

With this approach all operations (e.g. residual smoothing, multigrid etc.) are done on the new variables and not the conservative variables. The rationale is that since the pressure is more appropriate than density at lower speeds we should interpolate the pressure between grids rather than the density. Similarly, since the density is almost constant it is more beneficial to smooth the residual of the pressure rather than the residual of the density. The eigenvalues of this system, and hence the time steps needed for stability, are the same as for Algorithm I, (3.5).

5 Symmetric Preconditioner

Until now we have stressed the importance of preconditioning for low Mach number flows. Indeed we have constructed the preconditioners by starting from the incompressible equations and analyzing what changes are needed to the compressible equations in order to recover the incompressible equations in the limit. Van Leer, Lee and Roe [30] began at the other end. They first noticed that the two dimensional supersonic equations can be diagonalized if an appropriate preconditioner is added to the system. They then constructed a preconditioner for the subsonic case that it some sense was the continuation of the supersonic case. This continuation can never be exact since there must be a singularity at the sonic line.

Furthermore, in contrast to the variables that we have used until now van Leer et al. expressed the inviscid equations in $(\frac{dp}{\rho a}, du, dv, dS)$ variables. This differs from what we have done above in the normalization of the pressure variable. With this new set of variables the Jacobian matrices for inviscid flow are symmetric. Adding a symmetric positive definite preconditioner yields a symmetric hyperbolic system:

$$P^{-1}\frac{\partial w}{\partial t} + A\frac{\partial w}{\partial x} + B\frac{\partial w}{\partial y} = 0$$

where P, A, B are symmetric and P is positive definite. Taking the inner product with we have by integration by parts (ignoring boundary contributions) $(w, A\frac{\partial w}{\partial x}) = (w, B\frac{\partial w}{\partial x}) = 0$. Hence, we conclude that $\frac{\partial}{\partial t}(P^{-1}w, w) = 0$ and so $||w^2||_{P^{-1}}$ is constant in time. Since P^{-1} is positive definite, this norm is equivalent to the standard L^2 norm if there exists positive constants K_1 and K_2 such that

$$0 < K_1 \leq ||P|| \leq K_2$$

For the preconditioners that we shall consider the norm of P depends on the Mach number. Hence, we have well-posedness only as long as the Mach number is bounded away from zero. In the limit of the Mach number approaching zero, P becomes singular and the above analysis is no longer valid.

We now present the van Leer-Lee-Roe preconditioning for streamwise coordinates where the x axis is aligned with the flow and so $v = 0$. We express the preconditioner for the equations using $(\frac{dp}{\rho a}, du, dv, dS)$ variables. The coefficient matrices are given by

$$A = c\begin{pmatrix} M & 1 & 0 & 0 \\ 1 & M & 0 & 0 \\ 0 & 0 & M & 0 \\ 0 & 0 & 0 & M \end{pmatrix} \quad B = c\begin{pmatrix} 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 \\ 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \end{pmatrix}$$

Define $D = A\omega_1 + B\omega_2$; then

$$\mathbf{P}_V = \begin{pmatrix} \frac{\tau}{\hat\beta^2}M^2 & -\frac{\tau}{\hat\beta^2}M & 0 & 0 \\ -\frac{\tau}{\hat\beta^2}M & 1+\frac{\tau}{\hat\beta^2} & 0 & 0 \\ 0 & 0 & \tau & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

where

$$\hat\beta = \begin{cases} \sqrt{1-M^2} & M<1, \\ \sqrt{M^2-1} & M \ge 1 \end{cases}$$

$$\tau = \begin{cases} \sqrt{1-M^2} = \hat\beta & M<1, \\ \sqrt{1-M^{-2}} = \frac{\hat\beta}{M} & M \ge 1 \end{cases}$$

β was introduced to change the envelope of the wave form while τ was introduced to change the amplitude of the waves. More details of the development of this preconditioner are given in [34]. Hence, we include both in $\mathbf{P}_V$. The eigenvalues of $\mathbf{P}_V D$, for subsonic flow, are

$$\begin{aligned} \lambda_0 &= u\omega_1 \quad \text{twice} \\ \lambda_\pm &= \pm\tau M c\sqrt{\omega_1^2 + \frac{\omega_2^2}{1-M^2}} \end{aligned} \tag{5.1}$$

In order to compare this formula with the formulae of previous sections we wish to reformulate this preconditioner for the case where the flow is not aligned in the x direction. We denote the matrices in the streamwise and perpendicular directions as $A_\parallel$ and $A_\perp$ respectively. We next define the rotation matrices as

$$U = \begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & cos\theta & sin\theta & 0 \\ 0 & -sin\theta & cos\theta & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

$$U^{-1} = \begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & cos\theta & -sin\theta & 0 \\ 0 & sin\theta & cos\theta & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

To get the streamwise direction we shall choose

$$\begin{aligned} cos\theta &= \frac{u}{\sqrt{u^2+v^2}} \\ sin\theta &= \frac{v}{\sqrt{u^2+v^2}} \end{aligned}$$

One can then verify that given the original matrices A, B.

$$\begin{aligned} A_\parallel &= U(Acos\theta + Bsin\theta)U^{-1} \\ A_\perp &= U(-Asin\theta + Bcos\theta)U^{-1} \end{aligned}$$

Given numbers $\hat\omega_1, \hat\omega_2$ for $A_\parallel, A_\perp$ we define

$$\begin{aligned} \omega_1 &= \hat\omega_1 cos\theta - \hat\omega_2 sin\theta \\ \omega_2 &= \hat\omega_1 sin\theta + \hat\omega_2 cos\theta \end{aligned}$$

note $\hat{\omega_1^2} + \hat{\omega_1^2} = \omega_1^2 + \omega_2^2$.

Also define $\mathbf{P} = U^{-1}\hat{\mathbf{P}}U$. Then it is easy to verify that

$$\hat{\mathbf{P}}(A_\parallel\hat\omega_1 + A_\perp\hat\omega_2) = U\left[\mathbf{P}(A\omega_1 + B\omega_2)\right]U^{-1}$$

The van Leer-Lee-Roe preconditioning for general nonaligned flow in $(\frac{dp}{\rho a}, du, dv, dS)$ variables again decouples the last row and column. Hence we present only the 3×3 matrix:

$$\mathbf{P}_{VL} = \begin{pmatrix} \frac{\tau}{\hat\beta^2}M^2 & \frac{-\tau}{\hat\beta^2}u/a & \frac{-\tau}{\hat\beta^2}v/a \\ \frac{-\tau}{\hat\beta^2}u/a & b_{22} & b_{23} \\ \frac{-\tau}{\hat\beta^2}v/a & b_{23} & b_{33} \end{pmatrix}$$

$$\begin{aligned} b_{22} &= (\frac{\tau}{\hat\beta^2}+1)\frac{u^2}{u^2+v^2} + \tau\frac{v^2}{u^2+v^2} \\ b_{33} &= (\frac{\tau}{\hat\beta^2}+1)\frac{v^2}{u^2+v^2} + \tau\frac{u^2}{u^2+v^2} \\ b_{23} &= b_{32} = (\frac{\tau}{\hat\beta^2}+1)\frac{uv}{u^2+v^2} \end{aligned}$$

The symmetric preconditioner has the nice property that it always leads to a well posed problem, at least for Mach numbers bounded away from zero. It is also useful in constructing canonical forms that separate the Euler equations into its elliptic and hyperbolic constitute parts (see section 14). However, this preconditioner seems to have difficulties near stagnation points. One possible reason is that the general preconditioner depends on the flow angle even near stagnation points. However, for very small Mach numbers the angle the flow makes with the xaxis is not well defined. This leads to a numerical indeterminacy near stagnation points. Possible cures for this are discussed in [31]. These cures depend on modifications that remove this dependency on the flow angle usually at the cost of a loss of optimality.

In general it is not clear that a condition number of one at $M=0$ is a desirable trait. One purpose of preconditioning is to transform the infinite condition number at $M = 0$ to a finite and small condition number. However, in practice, choosing the optimal condition number of one results in a less robust scheme. Thus, for example, it is found that for Algorithm I and II (3, 4) that $\alpha = 0$ leads to a more robust scheme even though $\alpha = 1$ is optimal at $M = 0$. One possible reason for this is that the preconditioning affects not only the time step but also the artificial viscosity. An optimal preconditioning lowers the artificial viscosity which improves the accuracy but deteriorates the robustness of the scheme.

6 Convergence to the Incompressible Equations

The time dependent Euler equations can be written as

$$\begin{aligned} p_t + up_x + vp_y + \rho a^2(u_x + v_y) &= 0 \\ u_t + uu_x + vu_y + \frac{p_x}{\rho} &= 0 \\ v_t + uv_x + vv_y + \frac{p_y}{\rho} &= 0 \\ S_t + uS_x + vS_y &= 0 \end{aligned} \tag{6.1}$$

where a is the speed of sound given by $a^2 = \frac{\gamma p}{\rho}$.

The form of this system is unchanged if we nondimensionalize the equations. From now on we shall assume that u, v, p, ρ are nondimensional quantities where the dimensional variables are nondimensionalized by u_*, p_*, ρ_* with $p_* = \rho_* u_*^2$. Following [10] we define $\epsilon = \frac{u_*}{a_*} = M_*$. If the fluid is isentropic then

$$p = \frac{\rho^\gamma}{\gamma \epsilon^2} \quad , \quad a = \frac{\rho^{\frac{\gamma-1}{2}}}{\epsilon}. \tag{6.2}$$

Hence, as ϵ goes to zero the speed of sound, a, goes to infinity and so the first equation in (6.1) reduces to $u_x + v_y = 0$.

It was pointed out in [25, 26] that these equations can be symmetrized by using $\frac{dp}{\rho a}$ as the independent variable rather than dp. Hence, we define ϕ by $d\phi = \frac{dp}{\rho a}$. For isentropic flow both p and a are functions only of the density and so using (6.2) this can be integrated explicitly. This gives $\phi = \frac{\rho^{\frac{\gamma-1}{2}}}{\frac{\gamma-1}{2}\epsilon}$. As the Mach number goes to zero ϕ tends to infinity and therefore, Gustafsson and Stoor [10] subtract a constant and define

$$\phi = \frac{\rho^{\frac{\gamma-1}{2}} - 1}{\frac{\gamma-1}{2}\epsilon}. \tag{6.3}$$

This amounts to specifying the constant in the integration of $d\phi$ from dp. They then prove, using energy methods, that for the linearized equations

$$a\phi_x \rightarrow \frac{\partial p_{incompressible}}{\partial x}.$$

Hence, ϕ and all its derivatives behave as $O(M)$ as $M \rightarrow 0$. Since $\rho \rightarrow 1$ and using the definition of $d\phi$ this is equivalent to

$$dp_{compressible} \rightarrow dp_{incompressible}.$$

Several papers [10, 12, 14], have proven the convergence of the solution to the compressible equations to the solution of the incompressible equations, for isentropic flow, as the Mach number goes to zero. For nonisentropic flow there are no formal proofs. However, it is clear that for viscous flows that the boundary condition on the temperature, adiabatic or isothermal is very important.

All these results refer to the time dependent physical equations. Once preconditioning is introduced time accuracy is lost and one can only discuss convergence of the steady state solutions. In this case one would hope that the time dependent preconditioned compressible equations converge to some time dependent preconditioning of the incompressible equations. In addition, one would also want this to be true on the numerical level. Thus, one would want to solve the preconditioned compressible equations by some numerical technique, on a fixed mesh and compare that with the solution of the preconditioned incompressible equations on the same mesh. Mathematically, we have two limit processes occurring: the Mach number going to zero and the mesh size going to zero. These two limits need not commute. If one first converges the mesh size and then the Mach number it is equivalent to the convergence proofs for the analytic case. The more interesting problem is to converge the Mach number and then converge the mesh, i.e. we use a fix mesh as the Mach number is reduced.

In particular this requires a careful study of the viscosities introduced by the scheme. We first consider an upwinding scheme. For the compressible case the Riemann solver should depend on the preconditioned problem. One would then need to show that this Riemann problem converges to a Riemann problem for some preconditioning of the incompressible equations. We next consider a central difference scheme with a scalar viscosity. In this case a high order even difference of some quantity is added separately to each equation, e.g. for the incompressible equations: pressure for the continuity equation, u and v for the momentum equations. For the compressible equations one normally adds a density difference to the continuity equation. In such a case it is obvious that the numerical scheme for the compressible equations cannot converge to the numerical scheme for the incompressible equations. Furthermore, for low Mach number flows the density is almost constant and so the higher order difference of the density does not add much of a viscosity to the continuity equation. As such, we conclude that the artificial viscosity for the compressible continuity equation should be based on pressure and not density (at least for low Mach numbers).

By convergence of the compressible equations to the incompressible equations we are merely verifying what happens to the difference equations as the Mach number goes to zero. This gives necessary but not sufficient conditions for the convergence of the solution of the numerical approximation to the preconditioned compressible equations to the numerical solution of the incompressible equations. We consider a central difference approximation together with a scalar artificial viscosity for the nondimensionalized preconditioned inviscid equations. For the incompressible equations in nonconservative form we consider the preconditioned system

$$\begin{aligned} p_t+\beta^2(u_x+v_y) &= h\left[(K_1p_x)_x+(K_2p_y)_y\right] \\ \frac{u}{\beta^2}p_t+u_t+uu_x+vu_y+p_x &= h\left[(K_1u_x)_x+(K_2u_y)_y\right] \\ \frac{v}{\beta^2}p_t+v_t+uv_x+vv_y+p_y &= h\left[(K_1v_x)_x+(K_2v_y)_y\right] \end{aligned}$$

where each space derivative is approximated by a central difference with spacing h in each direction. We can also consider higher order accurate artificial viscosities but this doesn't change any of the properties that are of interest for the convergence to the incompressible limit. The time derivatives are replaced by a multistage scheme. K_1, K_2 are proportional to the largest eigenvalues of the coefficient matrix in the respective direction.

We next consider the same scheme for the preconditioned compressible inviscid equations, under the assumption that $p = p(\rho)$. It easier to analyze the convergence for the nonsymmetrical form since the pressure, p, converges and not $\frac{dp}{\rho a}$. Then for the compressible equations we have

$$\begin{aligned} p_t+\beta^2\left[(\rho u)_x+(\rho v)_y\right] &= h\left[(K_1p_x)_x+(K_2p_y)_y\right] \\ \frac{u}{\beta^2}p_t+u_t+uu_x+vu_y+\frac{p_x}{\rho} &= h\left[(K_1u_x)_x+(K_2u_y)_y\right] \\ \frac{v}{\beta^2}p_t+v_t+uv_x+vv_y+\frac{p_y}{\rho} &= h\left[(K_1v_x)_x+(K_2v_y)_y\right] \end{aligned}$$

Comparing these formulations it is obvious that if $\rho \to 1$ as $M \to 0$ then both converge to each other. It is crucial for both the time derivative and the artificial viscosity in the compressible continuity equation to be pressure based rather than density based. The preconditioning of the momentum equations is not important for this convergence.

We now consider how to construct a general artificial viscosity that will enable us to reach the incompressible limit without the difficulties previous presented. Consider

$$\mathbf{P}^{-1}w_t + f_x + g_y = h\left[(Q_1w_x)_x + (Q_2w_y)_y\right].$$

We wish to find the dependence of $\mathbf{P}$ and Q_i on the Mach number as $M \to 0$ so that we get the proper convergence. We therefore consider the isentropic equations based on $w = (\phi, u, v)$ (see (6.3)). This has the symmetric form

$$\mathbf{P}^{-1}w_t + \begin{pmatrix} a_{11} & a_{12} & a_{13} \\ a_{12} & a_{22} & a_{23} \\ a_{11} & a_{23} & a_{33} \end{pmatrix} w_x +$$

$$\begin{pmatrix} b_{11} & b_{12} & b_{13} \\ b_{12} & b_{22} & b_{23} \\ b_{11} & b_{23} & b_{33} \end{pmatrix} w_y = h\left[(Q_1w_x)_x+(Q_2w_y)_y\right]$$

As $M \to 0$ $a_{12}, b_{13} = O(1/M)$ while $d\phi = O(M)$ while all other quantities are bounded. Hence, the leading terms in the first equation are all $O(1/M)$ while they are $O(1)$ for the second and third equations. Multiplying the first equation by M and taking the limit we get $u_x + v_y$ for the space derivatives on the left hand side. Using $d\phi = O(M)$, $du = O(1)$, $dv = O(1)$ we see that a necessary condition for convergence as $M \to 0$ is that P^{-1}, Q_1, Q_2 all have the form

$$\mathbf{P}^{-1}, \mathbf{Q_1}, \mathbf{Q_2} \sim \begin{bmatrix} O(\frac{1}{M^2}) & O(\frac{1}{M}) & O(\frac{1}{M}) \\ O(\frac{1}{M}) & O(1) & O(1) \\ O(\frac{1}{M}) & O(1) & O(1) \end{bmatrix} \tag{6.4}$$

If we would have considered the variables (p, u, v) instead of (ϕ, u, v) then all the terms would have been of order 1. However, the matrices A, B would not be symmetric. Hence, each set has its advantages and we shall consider both sets of variables.

As an example, consider the equations in $(\frac{dp}{\rho c}, du, dv)$ variables. Then

$$\mathbf{A_{comp}} = \begin{pmatrix} u & c & 0 \\ c & u & 0 \\ 0 & 0 & u \end{pmatrix}, \mathbf{B_{comp}} = \begin{pmatrix} v & 0 & c \\ 0 & v & 0 \\ c & 0 & v \end{pmatrix}$$

Since these equations are nondimensionalized $c = O(1/M)$. Let

$$\mathbf{D} = A\omega_1 + B\omega_2 = \begin{pmatrix} Rq\omega_1 & \omega_1 c & \omega_2 c \\ \omega_1 c & Rq\omega_1 & 0 \\ \omega_2 c & 0 & Rq\omega_1 \end{pmatrix},$$

where $q^2 = u^2 + v^2$, $R = \frac{u\omega_1 + v\omega 2}{q}$ and we define $\mathbf{P^{-1}_{comp}}$ and $\mathbf{P_{comp}}$ by

$$\mathbf{P^{-1}} = \begin{pmatrix} \frac{2}{M^2} - 1 & \frac{u}{qM} & \frac{v}{qM} \\ \frac{u}{qM} & 1 & 0 \\ \frac{v}{qM} & 0 & 1 \end{pmatrix},$$

$$\mathbf{P} = \frac{1}{1-M^2} \begin{bmatrix} M^2 & -\frac{Mu}{q} & -\frac{Mv}{q} \\ \frac{-Mu}{q} & 1-M^2+\frac{u^2}{q^2} & \frac{uv}{q} \\ -\frac{Mv}{q} & \frac{uv}{q} & 1-M^2+\frac{v^2}{q^2} \end{bmatrix}$$

By inspection $\mathbf{P^{-1}_{comp}}$ has the form desired of (6.4). To find the form of the artificial viscosity we return to the numerical approximation for

$$\mathbf{P}^{-1}w_t + f_x + g_y = h\left[(Q_1 w_x)_x + (Q_2 w_y)_y\right] \quad .$$

For constant $\mathbf{P}$ we want $\mathbf{P}Q_1 = |\mathbf{P}A|$. Hence, $Q_1 = \mathbf{P^{-1}}|\mathbf{P}A|, Q_2 = \mathbf{P^{-1}}|\mathbf{P}B|$. Then

$$(\mathbf{P^{-1}}|\mathbf{PD}|)_{comp} =$$

$$q \begin{pmatrix} \frac{S+R}{M^2} & \frac{|u|R}{qM} & \frac{|v|R}{qM} \\ \frac{|u|R}{qM} & \frac{u^2|R|}{q^2} + \frac{v^2 S}{q^2(1-M^2)} & \frac{|uv|R}{q^2} - \frac{|uv|S}{q^2(1-M^2)} \\ \frac{|v|R}{qM} & \frac{|uv|R}{q^2} - \frac{|uv|S}{q^2(1-M^2)} & \frac{v^2|R|}{q^2} + \frac{u^2 S}{q^2(1-M^2)} \end{pmatrix}$$

$q^2 = u^2 + v^2$, $R = \frac{u\omega_1 + v\omega_2}{q}$, $S = \sqrt{(1-M^2)(1-M^2R^2)}$.

Letting $M \to 0$ we get $S \to 1$. To get the right limit of $(\mathbf{P^{-1}}|\mathbf{PD}|)_{comp}$ we must first multiply each element by the appropriate factor of M (or equivalently go to (p,u,v) variables). We then get

$$(\frac{dp}{\rho c}, du, dv)_{comp} \to (\frac{dp}{q}, du, dv)_{incomp}$$

and

$$(\mathbf{P^{-1}}|\mathbf{PD}|)_{comp} \to (\mathbf{P^{-1}}|\mathbf{PD}|)_{incomp} =$$

$$q \begin{pmatrix} |R|+1 & \frac{|uR|}{q} & \frac{|vR|}{q} \\ \frac{|uR|}{q} & \frac{u^2|R|+v^2}{q^2} & \frac{|uv|(|R|-1)}{q^2} \\ \frac{|vR|}{q} & \frac{|uv|(|R|-1)}{q^2} & \frac{v^2|R|+u^2}{q^2} \end{pmatrix}.$$

Changing from the variables $(\frac{dp}{q}, du, dv)_{incomp}$ to $(dp, du, dv)_{incomp}$ we get the same viscosity matrix given by Arnone and Turkel [3].

We next point out that the conditions on the matrix $(\mathbf{P^{-1}}|\mathbf{PD}|)_{\mathbf{comp}}$ are not satisfied by the nonpreconditioned Roe matrices. Furthermore, even reasonable preconditioners need not satisfy these conditions. Consider, for example, the one dimensional system

$$\mathbf{P^{-1}}w_t + Aw_x = h(Qw_x)_x.$$

A reasonable choice is $\mathbf{P^{-1}} = |A|$ i.e. $\mathbf{P} = |A^{-1}|$. In this case all the wave speeds of $\mathbf{P}A$ are ± 1. Now

$$Q = \mathbf{P}^{-1}|\mathbf{P}A| = |A|\,\left||A|^{-1}A\right| = |A| \sim$$

$$\begin{pmatrix} O(\frac{1}{M}) & O(1) & O(1) \\ O(1) & O(\frac{1}{M}) & O(1) \\ O(1) & O(1) & O(1) \end{pmatrix}$$

Q is the nonpreconditioned Roe matrix which does not have the desired property. We therefore conclude that for an upwind difference scheme the Riemann solver should be based on the preconditioned system and not the original scheme. For central difference schemes with a scalar artificial viscosity the viscosity in the continuity equation should include pressure terms. For a matrix viscosity $Q_1 = \mathbf{P^{-1}}|\mathbf{P}A|, Q_2 = \mathbf{P^{-1}}|\mathbf{P}B|$. Characteristics in the boundary conditions these should be based on the characteristics of the modified system and not the physical system. When using multigrid it is better to transfer the residuals based on the preconditioned system to the next grid since these residuals are more balanced than the physical residuals. However, conservation of the variables is now lost. Preconditioning is even more important when using multigrid than with an explicit scheme. With the original system the disparity of the eigenvalues greatly affects the smoothing rates of the slow components and so slows down the multigrid method, [16]. As indicated above there are accuracy difficulties at low Mach numbers [33]. Some of these can be alleviated by preconditioning the dissipation terms. For very small Mach numbers there is also a difficulty with round off errors as $\frac{p}{u^2+v^2} \to \infty$. Several people have suggested subtracting out a constant pressure from the dynamic pressure. A more detailed analysis [9] suggests replacing the pressure p by $\tilde{p}$ where $p = \frac{p_0 + \epsilon\tilde{p}}{\epsilon^2}$ and ϵ is a representative Mach number.

We conclude from the above remarks that the steady state solution of the preconditioned system may be different from that of the physical system.

Thus, on the finite difference level the preconditioning can improve the accuracy as well as the convergence rate.

7 Artificial Viscosity

We have seen that the details of the artificial viscosity (or equivalently the Roe matrix) determines whether the approximation to the compressible equation converges to that of the incompressible equations as the Mach number approaches zero. The preconditionings discussed i.e. Algorithm I, Algorithm II and Van Leer et. al. all satisfy the necessary condition (6.4). We have previously shown that the "natural" one dimensional preconditioning $P^{-1} = |A|$ does not satisfy (6.4). Similarly the preconditioner proposed by Allmaras though it has nice high frequency properties provides no help for the low Mach limit. We now present the implementation of the artificial viscosity in more detail.

7.1 Basic Dissipation Scheme

For a central difference scheme it is necessary to add artificial dissipative terms to the central difference approximation of the spatial derivatives. One usually adds a nonlinear second difference to control oscillations near shocks and a linear fourth difference to damp high frequency oscillations [11]. We are interested in the functional form of these differences. Hence, our examples will be with a second-difference artificial dissipation. Extensions to fourth differences and nonlinearities are straightforward. Similarly, for one sided schemes the central difference plus artificial dissipation is replaced by a Roe matrix formulation. Extension to these schemes is straightforward.

A preconditioned finite difference scheme can be expressed in differential form as

$$\begin{aligned} \Delta w_c &= \Delta t P \left[\frac{\partial F}{\partial x} + \frac{\partial G}{\partial y} \right] \\ &= \Delta t P \left[A \frac{\partial w_c}{\partial x} + B \frac{\partial w_c}{\partial y} \right] \end{aligned} \tag{7.1}$$

where w_c represents the conservation variables and the partial spatial derivatives are replaced by central difference approximations, either cell centered or at nodal points. We shall consider both conservative and non-conservative ways of adding artificial dissipative terms. The dissipation need not be expressed in terms of the conservative variables w_c. Using another set of variables w_V we have $\Delta w_c = \frac{\Delta w_c}{\Delta w_V} \Delta w_V$. Using different variables we can introduce the appropriate preconditioner in two ways. One choice is to completely change variables in all places and the matrices A and B in (7.1) change as well as the preconditioner P. The new preconditioner P_i is then a function of P_0, see (3.2), given by $P_i = \frac{\partial w_i}{\partial w_0} P_0 \frac{\partial w_0}{\partial w_i}$. An alternative is to leave the spatial derivatives in conservation form and to transform only the time derivatives. Essentially following Choi and Merkle's notation we denote this preconditioner by Γ (our Γ is the inverse of that used by Choi and Merkle). Thus, in conservative variables we have $\Gamma_c = P_c$. We choose as our "basic" form that given in (p, u, v, S) coordinates (i.e. P_0). Let w_c be the conservation variables then for any other set of variables we have $\Gamma_i = \frac{\partial w_i}{\partial w_c} P_c = P_i \frac{\partial w_i}{\partial w_c} = \frac{\partial w_i}{\partial w_0} P_0 \frac{\partial w_0}{\partial w_c}$.

We now include an artificial dissipation and replace (7.1) by differences in a general coordinate system (ξ, η) yielding:

$$\begin{aligned} \frac{\Delta (w_V)_{i,j}}{\Delta t} &= (\Gamma_V)_{i,j} \cdot \\ &\left[\frac{F_{i+1/2,j} - F_{i-1/2,j}}{\Delta \xi} + \frac{G_{i,j+1/2} - G_{i,j-1/2}}{\Delta \eta} \right] \\ &- \left[\frac{d_{i+1/2,j} - d_{i-1/2,j}}{\Delta \xi} + \frac{d_{i,j+1/2} - d_{i,j-1/2}}{\Delta \eta} \right] \end{aligned} \tag{7.2}$$

where

$$d_{i+1/2,j} = (|\sigma(PA)|)_{i+1/2,j} \left(w_{i+1,j} - w_{i,j} \right)$$

$$d_{i,j+1/2} = (|\sigma(PB)|)_{i,j+1/2} \left(w_{i,j+1} - w_{i,j} \right).$$

All variables refer to to V coordinates and $A_V = \frac{\partial w_V}{\partial w_c} A \frac{\partial w_c}{\partial w_V}$, B_V is defined similarly, and σ is matrix function. For example, if σ is proportional to the spectral radius then we have a scalar artificial viscosity, in w_V variables, while if $\sigma(A) \sim A$ we have a matrix-valued artificial viscosity. Once we have found Δw_V we can either update this to find w_V or else we can convert back to w_c variables to calculate Δw_c. Thus, for example, residual smoothing and multigrid can be done on either the w_c variables or the w_V variables.

Formula 7.2 is easy to implement. For a scalar viscosity (i.e. σ is a scalar function) the viscosity remains scalar after preconditioning. The main difference is that now differences of the w_V variables are added to each of the conservation variables rather than differences of the conserved variables. We note that in the original paper of Jameson, Schmidt and Turkel [11] differences of ρH rather than E were added to the energy equation. However, the formulation (7.2) is nonconservative. Since we are also be interested in transonic and supersonic flows with shocks we present the addition of the artificial dissipation in a conservative formulation. Furthermore, for internal flow the conservative form is important even for subsonic flows, without shocks, in order to preserve global quantities, e.g. total mass flow. A conservative formulation is then given by:

$$\frac{\Delta(w_V)_{i,j}}{\Delta t} = (\Gamma_V)_{i,j}\cdot$$

$$\left\{\frac{F_{i+1/2,j}-F_{i-1/2,j}}{\Delta\xi}+\frac{G_{i,j+1/2}-G_{i,j-1/2}}{\Delta\eta}\right. \tag{7.3}$$

$$\left.-\left[\frac{d_{i+1/2,j}-d_{i-1/2,j}}{\Delta\xi}+\frac{d_{ij+1/2}-d_{i,j-1/2}}{\Delta\eta}\right]\right\}$$

where

$$d_{i+1/2,j} =$$

$$\Gamma^{-1}_{i+1/2,j}\left(|\sigma(P_VA_V)|\right)_{i+1/2,j}\left[(w_V)_{i+1,j}-(w_V)_{i,j}\right]$$

$$d_{i,j+1/2} =$$

$$\Gamma^{-1}_{i,j+1/2}\left(|\sigma(P_VB_V)|\right)_{i,j+1/2}\left[(w_V)_{i,j+1}-(w_V)_{i,j}\right]$$

Even when σ is a scalar function we now have to evaluate matrix-vector product and so the numerical effort corresponds to a matrix-valued viscosity. We should mention that $A_V = \frac{\partial w_V}{\partial w_c}A\frac{\partial w_c}{\partial w_V}$, and similar expressions can be written for the other coordinate directions. Let $\hat{A_V} = \frac{\partial F}{\partial w_V}$ be the Jacobian matrix; then, $\hat{A_V} = \frac{\partial w_c}{\partial w_V}A_V$. Hence,

$$P_VA_V = \frac{\partial w_V}{\partial w_c}P_cA_c\frac{\partial w_c}{\partial w_V} = \Gamma_VA_c\frac{\partial w_c}{\partial w_V}$$

Because the spectral radius is invariant under a similarity transformation for a scalar viscosity, we can use either P_VA_V or P_cA_c. Let $\Lambda = \mathrm{diag}(\lambda_1,\lambda_2,\lambda_3,\lambda_3,\lambda_3)$, where λ_1,λ_2, and λ_3 represent λ_+,λ_- and λ_0 (i.e., the eigenvalues of PD), modified by cutoffs near the stagnation points. Define $|\Lambda| = \mathrm{diag}(|\lambda_1|,|\lambda_2|,|\lambda_3|,|\lambda_3|,|\lambda_3|)$. Then, $|PD| = R^{-1}|\Lambda|R$. For any vector $x = (x_1,x_2,x_3,x_4,x_5)^t$, $|PD|x = (R^{-1}|\Lambda|)z$, where $z = Rx$. Define $Y = \omega_1x_2+\omega_2x_3+\omega_3x_4$. Then,

$$z = \begin{pmatrix} \frac{1}{\lambda_+-\lambda_-}\left[\frac{\lambda_+-(1-\alpha)q}{\rho\beta^2}x_1+Y\right] \\ -z_1+\frac{x_1}{\rho\beta^2} \\ z_3 \\ z_4 \\ (1-\gamma)x_1+\frac{\gamma p}{T}x_5 \end{pmatrix}$$

where z_1 is the first element of the vector z. We note that z_3 and z_4 do not appear by themselves in subsequent formulas but rather in conjunction with other variables in the form

$$\omega_2z_3 = -x_2+\frac{1}{(\lambda_+-q)(\lambda_--q)}\left[\frac{\alpha(u|\omega|^2-q\omega_1)}{\rho}x_1-(\beta^2\omega_1-\alpha uq)Y\right]$$

$$\omega_2z_4 = -x_4+\frac{1}{(\lambda_+-q)(\lambda_--q)}\left[\frac{\alpha(w|\omega|^2-q\omega_3)}{\rho}x_1-(\beta^2\omega_3-\alpha wq)Y\right]$$

and

$$\omega_1z_3+\omega_3z_4 = x_3-\frac{1}{(\lambda_+-q)(\lambda_--q)}\left[\frac{\alpha(v|\omega|^2-q\omega_2)}{\rho}x_1-(\beta^2\omega_2-\alpha vq)Y\right]$$

Let

$$\begin{aligned} l_2 &= \frac{\beta^2\omega_1-\alpha u\lambda_+}{\lambda_+-q}|\lambda_1|z_1 \\ &+ \frac{\beta^2\omega_1-\alpha u\lambda_-}{\lambda_--q}|\lambda_1|z_2-(\omega_2z_3)|\lambda_3| \\ l_3 &= \frac{\beta^2\omega_2-\alpha v\lambda_+}{\lambda_+-q}|\lambda_1|z_1 \\ &+ \frac{\beta^2\omega_2-\alpha v\lambda_-}{\lambda_--q}|\lambda_1|z_2+(\omega_1z_3+\omega_3z_4)|\lambda_3| \\ l_4 &= \frac{\beta^2\omega_3-\alpha w\lambda_+}{\lambda_+-q}|\lambda_1|z_1 \\ &+ \frac{\beta^2\omega_3-\alpha w\lambda_-}{\lambda_--q}|\lambda_1|z_2-(\omega_2z_4)|\lambda_3| \end{aligned}$$

$$|PD|x = R^{-1}|\Lambda|z = \begin{bmatrix} \rho\beta^2(|\lambda_1|z_1+|\lambda_2|z_2) \\ l_2 \\ l_3 \\ l_4 \\ \frac{T}{\gamma p}\left[(\gamma-1)V_1+|\lambda_3|z_5\right] \end{bmatrix}$$

where V_1 is the first element of this vector.

For a scalar viscosity (i.e., when σ is the spectral radius), the viscosity remains scalar after preconditioning. In this approach, differences of the Q_V variables, rather than those of the conserved variables, are added to each of the conservation equations.

The formulation used until now is nonconservative. Since we are also interested in solving transonic flows with shocks using this scheme, we present a conservative formulation of the artificial dissipation. By dropping the subscript V, we obtain

$$\Delta Q = \Delta t \Gamma \left\{ \frac{\partial F}{\partial x} + \frac{\partial G}{\partial y} + \frac{\partial H}{\partial z} + \left(\Gamma^{-1} | \sigma(PA) | \frac{\partial Q}{\partial x} \right)_x + \left(\Gamma^{-1} | \sigma(PB) | \frac{\partial Q}{\partial y} \right)_y + \left(\Gamma^{-1} | \sigma(PC) | \frac{\partial Q}{\partial z} \right)_z \right\}$$

Even if σ is a scalar function, we must evaluate a matrix-vector product; as a result, the numerical effort is equivalent in complexity to a matrix-valued viscosity.

Following previous work on multigrid schemes for the Navier-Stokes equations, these artificial viscosity functions account for the ratio of the spectral radii in the different coordinate directions; that is,

$$\sigma(PA) = k^{(4)} \tilde{\sigma}(PA) \left[1 + \left(\frac{\rho(PB)}{\rho(PA)} \right)^\zeta + \left(\frac{\rho(PC)}{\rho(PA)} \right)^\zeta \right]$$

where $\tilde{\sigma}$ denotes the original viscosity function, ρ denotes the spectral radius, and $k^{(4)}$ is the artificial viscosity coefficient that corresponds to the fourth-difference terms. Similar relations are used to modify the artificial viscosity by cell aspect-ratio in the other coordinate directions. These scaling functions provide sufficient artificial dissipation for general curvilinear grids that contain high aspect-ratio cells.

In the previous section, a preconditioner was introduced that is dependent on the parameters α and δ. Because δ does not affect the eigenvalues of PA, it has no affect on the scalar artificial viscosity. Choosing $\alpha = 1$ reduces the largest eigenvalue, which also improves the condition number and decreases the artificial viscosity compared with $\alpha = 0$ case. We thus expect $\alpha = 1$ to slow the convergence compared with the case in which $\alpha = 0$, in spite of the fact that we have reduced the condition number. However, we expect that with $\alpha = 1$, the numerical accuracy will improve. For a matrix viscosity (or a Roe matrix), we expect similar but less pronounced dependence on α.

7.2 Preconditioned CUSP Scheme

In this section the use of specific dissipation schemes designed for shock capturing with a single-point shock structured is presented. More specifically, we describe the use of the *CUSP* scheme in combination with preconditioning.

We briefly review our previous description of *CUSP* for a Cartesian mesh. Extensions to a general mesh are straightforward.

$$\Delta w_c = \Delta t \left[\mathcal{L}_C + \mathcal{L}_{AD} \right], \tag{7.4}$$

where w_c represents the conservative variables. $\mathcal{L}_C$ is the central difference approximation to the inviscid flux balance (possibly also including the physical viscous Navier-Stokes terms) while $\mathcal{L}_{AD}$ represents the artificial dissipation as a linear combination of second differences of the state vector w and F where F is the flux through a cell face.

$$\mathcal{L}_{AD} = -\left[\frac{d_{i+1/2,j} - d_{i-1/2,j}}{\Delta x} + \frac{d_{i,j+1/2} - d_{i,j-1/2}}{\Delta y} \right]$$

$$d_{i+1/2,j} = \frac{\nu c}{2}(w_{i+1,j} - w_{i,j}) + \frac{\beta}{2}(F_{i+1/2,j} - F_{i,j})|\vec{S}|$$

The dissipation coefficients, ν and β, can be defined such that a steady-state shock structure with a single interior point is obtained for shocks aligned with the cell face $(i + 1/2, j)$. The particular form chosen for these parameters supports a clean shock capturing provided that the convective cell face Mach number is larger than 0.5. Moreover, it was shown that the eigenvalues of the artificial viscosity matrix are all equal to the convective cell face velocity for Mach numbers less than 0.5.

These observations yield sufficient guidance for the selection of appropriate preconditioning parameters for *CUSP*: First, the preconditioning matrix, P_c should be turned off within the shock structure so that the shock capturing properties of the *CUSP* scheme are not perturbed. This is accomplished with the choice $\alpha = 0, M_0 = 0.5$ in (3.3). The nonconservative preconditioned *CUSP* can then be written as

$$\Delta w_c = \Delta t \left[P_c \mathcal{L}_C + \mathcal{L}_{AD} \right], \tag{7.5}$$

Note, that we use conservative w_c variables and not (p, u, v, T) variables. The nonconservative form should give clean shocks if the post-shock Mach number is larger than 0.5. This is true, in particular, for transonic flows which create only moderate strength shocks. However, low post-shock Mach numbers can be observed for hypersonic flows. This is a partial motivation for considering a conservative form for the dissipation. This conservative is given by

$$\Delta w_c = \Delta t P_c \left[\mathcal{L}_C - \left((P_c w)_{i+1/2,j} - (P_c w)_{i-1/2,j} \right) - \left((P_c w)_{i,j+1/2} - (P_c w)_{i,j-1/2} \right) \right]$$

This form is conservative for all Mach numbers. The shock capturing analysis holds for all cell faces where the local Mach number is larger than 0.5 and so $P_c = I$. Hence, this preconditioned scheme is consistent with the basic *CUSP* scheme formulation. The disadvantage of the conservative formulation is that it is more expensive than the nonconservative form since P_c must be calculated at each of the neighbors $(i+1/2,j)$ etc. and a matrix-vector multiply is needed at each neighbor rather than just at the single point (i,j) for the nonconservative formulation.

8 Boundary Conditions

In many codes the boundary conditions in the far field are based on characteristic variables, even for viscous flow. Thus at inflow the incoming variables, corresponding to positive eigenvalues, are specified while the outgoing variables, corresponding to negative eigenvalues, are extrapolated. Once we change the time dependent equations we also change the characteristics of the system (though not the signs of the eigenvalues). Hence, it is necessary to also modify the boundary conditions for the preconditioned system. In addition, the original characteristic variables do not scale correctly as the Mach goes to zero and so we do not obtain well-posed boundary conditions in the limit.

Since the eigenvalues and eigenvectors are invariant under a similarity transform we shall use the (p,u,v,S) set of variables to determine the new eigenvalues and characteristic variables. We shall only consider the flow normal to the boundary which we take to be a line $x = const$. Thus, we need to use the characteristic variables we found above corresponding to the left eigenvectors of P_0A_0. Flow variables at a boundary are then obtained by taking the values for R_1, R_2 and R_+ from upstream flow whereas downstream values are used for R_-. When we diagonalize $P_0A_0 = RDR^{-1}$ the rows of R are the left eigenvectors of P_0A_0 while the columns of R^{-1} are the right eigenvectors of P_0A_0. Let variables with a subscript "b" denote the variables to be computed at the boundary. Variables with a subscript "a" denote the flow state approaching the boundary, i.e. specified at inflow, whereas variables with a subscript "l" are used for the flow leaving the boundary, e.g. extrapolated at inflow. Note, that this notation can be consistently used for inflow and outflow boundaries. The characteristic boundary conditions are expressed in (p,u,v,T) variables as:

$$
\begin{aligned}
p_b = {} & \frac{\lambda_+ p_a - \lambda_- p_l}{\lambda_+ - \lambda_-} - \\
& \frac{1}{\lambda_+ - \lambda_-}\left[u(1-\alpha-\delta\frac{(\gamma-1)\beta M_r^2}{a^2})(p_a-p_l)\right. \\
& \left. -\rho\beta M_r^2(u_a-u_l) + \frac{\delta\rho\beta M_r^2 u}{T}(T_a-T_l)\right]
\end{aligned}
$$

$$
\begin{aligned}
u_b &= u_a - \frac{\lambda_+ - u(1-\alpha)}{\rho\beta M^2}(p_b-p_a) \\
T_b &= T_a + \frac{(\gamma-1)T}{\gamma p}(p_b-p_a) \\
v_b &= v_a - \frac{\alpha v}{\beta M^2 - \alpha u^2}\left[\frac{p_b-p_a}{\rho} + u(u_b-u_a)\right]
\end{aligned}
\tag{8.1}
$$

In generalized coordinates u and v are replaced by the normal and tangential components of the velocity relative to the boundary.

Computationally we observed that a simplified set of non-characteristic conditions yielded almost the same results as those of the characteristic boundary conditions. These are given by

$$v_b = v_a, \quad p_b = p_l, \quad u_b = u_a,$$

either $T_b = T_a$ or $\rho_b = \rho_a + \frac{p_b - p_a}{a^2}$ The simplified boundary condition has been used in all of the computations.

These boundary conditions are reasonable for exterior problems. However, for flow in interior regions one customarily specifies the total temperature, T_t, and total pressure, p_t, profiles together with the angle of the flow at inflow. At the exit a back pressure is usually given. Let

$$
\begin{aligned}
\frac{T_t}{T} &= 1 + \frac{\gamma-1}{2}M^2 \\
\frac{p_t}{p} &= \left\{1 + \frac{\gamma-1}{2}M^2\right\}^{\frac{\gamma-1}{\gamma}} \\
\tan(\theta) &= \frac{v}{u}
\end{aligned}
$$

A reasonable boundary treatment for the inflow boundary is

$$
\begin{aligned}
p_b &= p_l \\
T_b &= T_t\left(\frac{p_b}{p_t}\right)^{\frac{\gamma-1}{\gamma}} \\
u_b^2 &= \frac{\frac{2\gamma}{\gamma-1}(T_t - T_b)}{1+\tan^2(\theta)} \\
v_b &= u_b \tan(\theta)
\end{aligned}
$$

At the exit we specify the back pressure and extrapolate u, v, T.

9 Implementation

We present the steps used to introduce preconditioning into a previously existing code based on Algorithm I. For simplicity we shall assume an explicit iteration scheme (e.g. Runge-Kutta) possibly augmented by implicit residual smoothing and multigrid.

1. Precondition the residual

   - Select a reasonable set of variables for the problem e.g. (p, u, v, T). We stress that other sets of variables are possible. This set is used for illustration only.
   - For nonconservative scalar artificial viscosity
     - multiply physical residual (inviscid and Navier-Stokes portions and physical forcing functions (if applicable)) by $\Gamma = P_T \frac{\partial w_4}{\partial w_1}$.
     - add scalar artificial viscosity in these new variables to the residual.
   - For conservative scalar viscosity
     - viscosity includes Γ^{-1} (see (7.3)). Hence, even a scalar viscosity requires a matrix-vector multiply.
     - add inviscid, viscous and artificial viscosity fluxes to obtain the total residual.
     - multiply this total residual by Γ.

2. Perform residual smoothing. At the end of the Runge-Kutta cycle restrict the residual to the next coarser grid. Thus both residual smoothing and restrictions are performed on the residuals in (p, u, v, T) variables.

3. Having calculated the total preconditioned residual in (p, u, v, T) multiply these by Δt. There are then two ways of updating the solution to the next Runge-Kutta stage.

   - One: multiply the above total residual by $\frac{\partial w_1}{\partial w_4}$ to get the residual in conservative variables. Add the new residual to the old conservative variables to get new conservative variables.
   - Two: Add the residuals in (p, u, v, T) variables to the old (p,u,v,T) variables to get (p, u, v, T) at the next Runge-Kutta stage. Calculate the conservative variables as nonlinear functions of (p, u, v, T).

4. Choose a new time step based on the preconditioning (3.4).

5. Modify the far field boundaries based on the new characteristics. If characteristic data is also used at physical boundaries (e.g. inflow to a nozzle) these should also be modified. Alternatively, specify or extrapolate (p, u, v, T) at the boundaries.

For Algorithm II (4) all operations including residual smoothing and interpolations between grids are done in terms of the $(p', \rho u, \rho v, E')$ variables. This scheme has the advantage that, in theory, setting $M_\infty = 0$ would yield identical results to an incompressible code based on pseudo-compressibility. Algorithm I as presently implemented performs the residual smoothing and restriction in terms of (p, u, v, T) variables. However, restriction of the variables rather than residuals for the FAS algorithm is based on conservative variables. Similarly the prolongation from coarse to fine grids is based on conservative variables.

10 Jacobi Preconditioning

Consider the semi-discrete approximation

$$\begin{aligned} w_t &= \frac{f_{i+1/2,j} - f_{i-1/2,j}}{2\Delta x} + \frac{g_{i,j+1/2} - g_{i,j-1/2}}{2\Delta y} \\ &\quad + \frac{1}{2}\left\{\Delta_x(|A|\Delta_x w) + \Delta_y(|B|\Delta_y w)\right\} \end{aligned}$$

where Δ are appropriate finite difference operators. A and B are the Jacobians of f and g with respect to w respectively. Linearizing and taking Fourier transforms we get

$$\begin{aligned} G(\theta, \phi) &= i\,(A\sin(\theta) + B\sin(\phi)) \\ &\quad - |A|(1 - \cos(\theta)) - |B|(1 - \cos(\phi)) \end{aligned}$$

and so

$$G(\pi, \pi) = -2|A| - 2|B| \tag{10.1}$$

It is difficult to choose coefficients in a Runge-Kutta scheme that will damp all the eigenvalues of the matrix $G(\pi, \pi)$. Instead Allmaras [1, 2] and later Pierce-Giles [18] suggest replacing (10.1) by

$$\begin{aligned} \frac{(|A| + |B|)}{\rho(A) + \rho(B)} w_t &= \frac{f_{i+1/2,j} - f_{i-1/2,j}}{2\Delta x} \\ &\quad + \frac{g_{i,j+1/2} - g_{i,j-1/2}}{2\Delta y} \\ &\quad + \frac{1}{2}(\Delta_x(|A|\Delta_x w + \Delta_y(|B|\Delta_y w) \end{aligned} \tag{10.2}$$

where $\rho(A)$ is the spectral radius of A. (10.1) is now replaced by

$$G(\pi,\pi) = -2\rho(A) - 2\rho(B)$$

Hence, at the highest frequency G is essentially a scalar and so one can choose Runge-Kutta coefficients to damp this scalar quantity.

11 Preconditioning-squared

The Jacobi preconditioning (10.2) does nothing to improve the condition number of the system for low Mach numbers. On the other hand the low Mach number preconditioner (3.2) was not constructed to treat high frequencies errors. Hence, one can combine the two approaches and replace (10.2) by

$$2\frac{(|PA|+|PB|)}{\rho(PA)+\rho(PB)}w_t =$$
$$P\left\{\frac{f_{i+1/2,j}-f_{i-1/2,j}}{\Delta x} + \frac{g_{i,j+1/2}-g_{i,j-1/2}}{\Delta y}\right.$$
$$\left. + \Delta_x(P^{-1}|PA|\Delta_x w) + \Delta_y(P^{-1}|PB|\Delta_y w)\right\}$$

12 Time Dependent Problems

We consider two kinds of time dependent problems. For one, which is typified by acoustic problems, the requirements of accuracy and stability are approximately the same. Thus, the time restrictions required by stability of the scheme do not impose an unnecessary burden on the scheme as the same time steps are needed to resolve the changes in the time behavior of the scheme. For such problems explicit methods are the best. It is not clear how to combine this with preconditioning since the preconditioning that we have discussed until now destroys the time accuracy of the method.

A second time dependent problem is one where the time steps required by accuracy are much larger than those required by stability. One application is to forced motion where the time scale of the outside forces are much larger than the stability time step of an implicit scheme. For such problems it is useful to introduce an implicit method. However, to avoid time errors associated with large time steps it is advisable to use a fully implicit method and not an ADI type algorithm. However, this leads to the necessity of inverting large non-sparse matrices for a linear problem plus the linearization difficulties of a non-linear problem. One alternative is to consider the implicit method as a steady state problem for the next time step. Thus, any steady solver can be used to go from time t to time $t + \delta t$. It is only required that the steady state solver converge within a short enough time that this approach is more efficient than a straightforward explicit method. Thus, for example, if accuracy requirements lead to a CFL of 100 relative to an explicit method then this approach is efficient if we can solve for the steady state in 50 iterations or less. In order for this to be feasible it is necessary to start with a good initial guess which can be obtained by extrapolation from previous time data. In addition we only want the steady state solver to converge to the discretization level of the time dependent implicit scheme. Any attempt to solve the steady state problem to lower residuals is a waste of time.

As an example consider the simple time dependent problem

$$\frac{\partial w}{\partial t} + \frac{\partial f}{\partial x} = 0$$

We discretize this equation by the backward Euler method which is only first order in time.

$$w^{n+1} + \delta t(\frac{\partial f}{\partial x})^{n+1} = w^n$$

To solve this problem we introduce a pseudo-time variable τ and solve

$$w_\tau + \frac{w}{\delta t} + \frac{\partial f}{\partial x} = \frac{w^n}{\delta t}$$

until a steady state in τ is reached. At this level we can now introduce preconditioning into the system and replace w_τ by $P^{-1}w_\tau$ as before.

13 Differential Preconditioners

We consider the linearized equations with constant coefficients. We first rewrite (6.1) in differential form. The Euler equations can be written as

$$w_t + \mathcal{L}w = 0 \tag{13.1}$$

with $w = (p,u,v,S)^t$. Define

$$Q = u\partial_x + v\partial_y$$

Since, all coefficients are assumed constant Q commutes with ∂_x and ∂_y and

$$\mathcal{L} = \begin{pmatrix} Q & \rho c^2\partial_x & \rho c^2\partial_y & 0 \\ \frac{1}{\rho}\partial_x & Q & 0 & 0 \\ \frac{1}{\rho}\partial y & 0 & Q & 0 \\ 0 & 0 & 0 & Q \end{pmatrix} \tag{13.2}$$

Let

$$D = Q^2 - c^2(\partial_x^2 + \partial_y^2). \tag{13.3}$$

We now replace (13.1) by the preconditioned system

$$w_t + \mathbf{P_D}\mathcal{L}w = 0 \tag{13.4}$$

with

$$\mathbf{P_D} = \begin{pmatrix} Q^2 & -\rho c^2\partial_x Q & -\rho c^2 \partial_y Q & 0 \\ -\frac{1}{\rho}\partial_x & Q^2 - c^2\partial_y^2 & c^2\partial_x\partial_y & 0 \\ -\frac{1}{\rho}\partial_y & c^2\partial_x\partial_y & Q^2 - c^2\partial_x^2 & 0 \\ 0 & 0 & 0 & D \end{pmatrix}$$

One can then verify that

$$\mathbf{P_D}\mathcal{L} = QD\mathbf{I}, \qquad \mathbf{P}_D^{-1} = D^{-1}Q^{-1}\mathcal{L}$$

One can replace the D in the lower right corner of $\mathbf{P}_D$ by the identity matrix. Then $\mathbf{P_D}\mathcal{L}$ is not the identity matrix but is still a diagonal matrix. We can use simpler matrices than $\mathbf{P}_D$ by considering congruent transformations. Consider the symmetrizing variables $(\frac{dp}{\rho c}, u, v, S)$, then

$$\mathcal{L} = \begin{pmatrix} Q & c\partial_x & c\partial_y & 0 \\ c\partial_x & Q & 0 & 0 \\ c\partial y & 0 & Q & 0 \\ 0 & 0 & 0 & Q \end{pmatrix}$$

Let,

$$\mathbf{P_E} = \begin{pmatrix} Q & -c\partial_x & -c\partial_y & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

$$\mathbf{P_E^t} = \begin{pmatrix} Q & 0 & 0 & 0 \\ -c\partial_x & 1 & 0 & 0 \\ -c\partial_y & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

then

$$\mathbf{P_E}\mathcal{L}\mathbf{P_E^t} = \begin{pmatrix} DQ & 0 & 0 & 0 \\ 0 & Q & 0 & 0 \\ 0 & 0 & Q & 0 \\ 0 & 0 & 0 & Q \end{pmatrix}$$

so we have diagonalized $\mathcal{L}$ by a congruent transformation. But,

$$\mathbf{P_E}\mathcal{L}\mathbf{P_E}^t = \mathbf{P_E^{t^{-1}}}(\mathbf{P_E^t}\mathbf{P_E}\mathcal{L})\mathbf{P_E},$$

so the congruent transform is similar to a preconditioning with a positive definite matrix $\mathbf{P_E^t}\mathbf{P_E}$. Alternatively, $(\mathbf{P_E^t}\mathbf{P_E})\mathcal{L}$ is similar to a diagonal matrix.

$$\mathbf{P_E^t}\mathbf{P_E} = \begin{pmatrix} Q & -c\partial_x & -c\partial_y & 0 \\ -c\partial_x & 1 + c^2\partial_x^2 & c^2\partial_x\partial_y & 0 \\ -c\partial_y & c^2\partial_x\partial_y & 1 + c^2\partial_y^2 & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

Note that $\mathbf{P_E^t}\mathbf{P_E}$ looks similar to $\mathbf{P_D}$ but is not identical. $\mathbf{P_E^t}\mathbf{P_E}$ has fewer derivatives along the identical but $\mathbf{P_E^t}\mathbf{P_E}\mathcal{L}$ is only similar to a diagonal matrix while $\mathbf{P_D}\mathbf{L}$ is diagonal and even a scalar differential operator multiplying the identity matrix. These transformations are independent of the flow regime as long as the preconditioner is nonsingular.

It remains to show that $\mathbf{P}$ is nonsingular. We have four eigenvalues and corresponding eigenfunctions. As usual the entropy wave decouples. For this wave $\mathbf{P}$ has an eigenvalue D and an eigenfunction (0,0,0,1) . For the shear wave $\mathbf{P}$ has an eigenvalue D and the eigenvector is $(v_1, v_2, v_3, 0)$ where

$$Dv_1 = 0$$

$$D(\frac{\partial v_2}{\partial x} + \frac{\partial v_3}{\partial y}) = 0$$

The other two 'acoustic' eigenvalues of $\mathbf{P}$ are $Q^2 \pm cQ\sqrt{\partial_x^2 + \partial_y^2}$ and the eigenvectors satisfy the pseudo-differential equation

$$\left[c(\partial_x^2 + \partial_y^2) \pm Q\sqrt{\partial_x^2 + \partial_y^2}\quad\right]\left(\frac{\partial v_3}{\partial x} - \frac{\partial v_2}{\partial y}\right) = 0$$

$$\mp\sqrt{\partial_x^2 + \partial_y^2} = \rho c\left(\frac{\partial v_2}{\partial x} + \frac{\partial v_3}{\partial y}\right)$$

We therefore have to show that the eigenvalues are all nonzero so that $\mathbf{P}$ is nonsingular. The operator D is just the potential operator i.e. for any variable w

$$Dw = (u^2 - c^2)w_{xx} + 2uvw_{xy} + (v^2 - c^2)w_{yy}$$

For subsonic flow this is an elliptic operator and so invertible. For supersonic flow D is a hyperbolic operator . Similarly, Q is a hyperbolic operator denoting convection along a streamline. Thus, given appropriate boundary conditions this too should be invertible. At a stagnation point Q is singular and so it is necessary to limit the values of u and v in the definition of Q so that they do not become too small in a neighborhood of the stagnation point. A similar smoothing is needed near the sonic line.

With residual smoothing and $\mathbf{P_D}$ we have increased the order of the system and so changed the number of boundary conditions needed for the equation to be well posed. To avoid this difficulty we do not solve the equation (13.4). Instead these preconditioners are used as a post processor for the usual Euler or Navier-Stokes equations. Thus, at each time step we calculate a residual based on one's favorite scheme. This gives a predicted value of the change in time, $\Delta w_{predicted}$. We also update the boundary conditions for the standard fluid dynamic equations. We then operate on Δw with $\mathbf{P}$ with the boundary condition that $\Delta w_{corrected} = 0$, i.e. we don't change the boundary values calculated by the predictor. When we reach a steady state for the fluids equations we are solving $\mathbf{P}\Delta w_{corrected} = 0$ with zero boundary conditions. Since $\mathbf{P}$ is invertible $\Delta w = 0$, i.e. we preserve the steady state. Thus, in essence we are imposing the fluid dynamic boundary conditions between the $\mathbf{P}$ operator and the $\mathcal{L}$ operator.

We note that if the partial derivatives are all replaced by central differences then everything goes over since it is based only a formal multiplication and uses no properties of the derivative. Hence, beginning with a central difference approximation to the constant coefficient multidimensional Euler equations we can precondition it so that we have a set of scalar equations. This applied equally well for any aspect ratio. Hence, we need consider high aspect ratio problems only for the scalar equation. This use of the differential preconditioner is similar to the explicit/implicit residual averaging previously considered except that now the explicit portion is a matrix involving second differences rather than the scalar second differences considered before.

14 Canonical Decomposition

We shall restrict our analysis to the linear case with constant coefficients. Our typical system is either a steady state problem $\mathcal{L}u = 0$ or the unsteady problem $u_t + \mathcal{L}u = 0$. When diagonalizing such a system we distinguish between three types of diagonalization.

1. A similarity transformation is introduced so that $Q\mathcal{L}Q^{-1}$ is diagonal. In this case if we define $\mathbf{v} = Q\mathbf{u}$ then we have a diagonal system for the variables $\mathbf{v}$. Hence, this is equivalent to a change of variables.

2. We precondition the unsteady problem to get $\mathbf{P}^{-1}u_t + \mathcal{L}u = 0$ where $\mathbf{P}$ is positive definite and $\mathcal{L}$ is symmetric. We now assume a decomposition $\mathbf{P} = TS$ and define $v = T^{-1}u$. Then the equation becomes $v_t + (S\mathcal{L}T)v = 0$. A particular case is when $S = T^*$. This is convenient since every positive matrix $\mathbf{P}$ has the decomposition $\mathbf{P} = TT^*$. In this case we have a congruence transformation of $\mathcal{L}$. Hence, preconditioning is equivalent to a11 congruence transformation plus a similarity transformation.

3. In the above two cases we have implicitly assumed that the transformation Q contains only constant coefficients and not differential operators. Hence, we are not changing the order of the differential system. A different approach is to allow the transformations to depend on derivatives. This is equivalent to replacing the first order system by a set of higher order equations. This again can be done via a change of variables, i.e. a similarity transform or else via a preconditioning i.e. a congruence transform.

In all these cases we demand that the steady state solution be independent of the transformations used so that either a similarity or congruence transformation may be allowed.

We first consider equations in one space direction plus time so that $\mathcal{L} = A\partial_x$. In this case any strongly hyperbolic $(m \times m)$ system of the form

$$\partial_t \mathbf{u} + A\partial_x \mathbf{u} = 0$$

is reducible to m scalar convection equations of the form

$$\partial_t(\ell_k \cdot \mathbf{u}) + \lambda_k \partial_x(\ell_k \cdot \mathbf{u}) = 0$$

where ℓ_k is a left eigenvector of A, and λ_k is the corresponding eigenvalue. This follows since for a strongly hyperbolic system A is diagonalizable. Thus, the canonical form is simply the familiar linear advection equation

$$\partial_t u + a\partial_x u = 0$$

In two dimensions we consider first the steady-state equations

$$A\partial_x u + B\partial_y u = 0 \tag{14.1}$$

When A and B are symmetric it is known that this equation can be diagonalized by a congruence transformation if and only if some real linear combination of A and B is positive definite. In that case the canonical form is again linear advection

$$a\partial_x u + b\partial_y u = 0. \tag{14.2}$$

If the above condition is not met, then we shall show that some of the eigenvalues of $A^{-1}B$ appear in conjugate pairs, and a second canonical form appears which is a (2×2) system, equivalent under scaling and axis transformations to the Cauchy-Riemann equations

$$\begin{pmatrix} 1 & 0 \\ 0 & -1 \end{pmatrix} \partial_x \begin{pmatrix} u \\ v \end{pmatrix} - \begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix} \partial_y \begin{pmatrix} u \\ v \end{pmatrix} = 0.$$

The general two-dimensional system can then be written in a form that is block diagonal, with a mixture of scalar and (2×2) blocks. When the steady solution is sought by marching in a time-like variable, we show that a preconditioning matrix P can always be found, such that this block structure is preserved in the transient solution of

$$\mathbf{P}^{-1}\partial_t \mathbf{u} + A\partial_x \mathbf{u} + B\partial_y \mathbf{u} = 0$$

The scalar blocks have then the canonical form

$$\partial_t u + a\partial_x u + b\partial_y u = 0. \tag{14.3}$$

The (2×2) blocks, although they behave elliptically in the steady state, behave hyperbolically in the transient phase, and the associated variables follow a wave equation

$$\frac{\partial^2 \psi}{\partial t^2} = \frac{\partial^2 \psi}{\partial x^2} + \frac{\partial^2 \psi}{\partial y^2} \tag{14.4}$$

We consider (14.3) and (14.4) as our basic canonical forms. Although both of these equations are hyperbolic, considered as time-dependent problems, only (14.3) is associated with any distinct direction (namely $dy/dx = b/a$). By contrast, (14.4), during the transient phase, is associated with characteristic surfaces, $(x - x_0)^2 + (y - y_0)^2 - (t - t_0)^2 = const$, rather than with individual directions. In the steady state, (14.3) is a hyperbolic equation while (14.4) reduces to an elliptic equation, Laplace's equation, and so has no uniquely distinguished directions.

In three dimensions, we have three canonical forms, which are

$$\frac{\partial \psi}{\partial t} + a\frac{\partial \psi}{\partial x} + b\frac{\partial \psi}{\partial y} + c\frac{\partial \psi}{\partial z} = 0,$$

and (3×3) systems equivalent to either

$$\frac{\partial^2 \psi}{\partial t^2} = \frac{\partial^2 \psi}{\partial x^2} + \frac{\partial^2 \psi}{\partial y^2} + \frac{\partial^2 \psi}{\partial z^2},$$

or

$$\left(\frac{\partial}{\partial t} - \frac{\partial}{\partial x}\right)^2 \psi = \frac{\partial^2 \psi}{\partial y^2} + \frac{\partial^2 \psi}{\partial z^2},$$

15 The Two dimensional Case

15.1 General Steady-state Problems

We consider

$$A\partial_x u + B\partial_y u = 0 \tag{15.1}$$

with A and B symmetric. This is a reasonable assumption since many physical systems can be described by symmetric hyperbolic equations.

According to a result of Au-Yeung [4] this equation can be diagonalized by a congruence transformation if a real linear combination of A and B is positive definite. In the present context, this condition has a physical interpretation. Suppose that we add a time-dependent term $\partial_t u$ to (15.1). Then the speeds with which waves propagate in a direction θ are the eigenvalues of $A\cos\theta + B\sin\theta$. If this matrix is positive definite for $\theta = \theta^*$, then the domain of influence of a disturbance at the origin lies in the half-plane $x\cos\theta^* + y\sin\theta^* > 0$. Therefore the domain of influence does not enclose the origin, and tangents to it from the origin may be drawn. These are the characteristic directions for the steady solution. This situation arises whenever the flow speed is greater than the speed of any signal relative to the medium (supersonic case). Thus, the two dimensional supersonic flow equations are always diagonalizable.

To deal with the subsonic case, we begin by attempting a formal diagonalization of (15.1). We premultiply the equation by a matrix S, and effect a change of variable $Qv = u$, so that

$$(SAQ)\partial_x v + (SBQ)\partial_y v = 0. \tag{15.2}$$

We require that SAQ, SBQ be representable as

$$\begin{aligned} SAQ &= \Lambda_A^{\#}, \\ SBQ &= \Lambda_B^{\#}, \end{aligned}$$

where $\Lambda_A^{\#}, \Lambda_B^{\#}$ denote matrices having the same block diagonal structure. (Note that matrices sharing such a structure form a closed group under multiplication and inversion.) Then

$$(\Lambda_A^{\#})^{-1}\Lambda_B^{\#} = (Q^{-1}A^{-1}S^{-1})(SBQ) = Q^{-1}A^{-1}BQ$$

so that Q must represent a similarity transformation that block diagonalises $A^{-1}B$. (If A happens to be singular we may diagonalize $B^{-1}A$ instead). At the present stage, the matrix S is still arbitrary. We first attempt a complete diagonalization.

$$A^{-1}B = R\Lambda L \qquad \text{where} \qquad R = L^{-1}$$

If this succeeds, we can take $S = LA^{-1}$ and $Q = R$, to derive

$$\partial_x(Lu) + \Lambda\partial_y(Lu) = 0.$$

representing a set of characteristic equations for the characteristic variables $\mathbf{v}_k = \ell_k \cdot \mathbf{u}$ propagating along directions $dy/dx = \lambda_k$. This is a similarity transformation that reduces A to the identity matrix and diagonalizes B.

Suppose this fails in that

$$\det(A^{-1}B - \lambda I) = 0$$

has a pair of conjugate roots

$$\lambda_{1,2} = \lambda_R \pm i\lambda_I.$$

Then we will also find conjugate eigenvectors

$$\begin{aligned} \mathbf{r}_{1,2} &= \mathbf{r}_R \pm i\mathbf{r}_I, \\ \ell_{1,2} &= \ell_R \pm i\ell_I. \end{aligned}$$

That is,

$$A^{-1}B = \begin{bmatrix} \cdot & \cdot & & & \\ \cdot & \cdot & & & \\ r_1 & r_2, & \cdot & \cdot & \cdot \\ \cdot & \cdot & & & \\ \cdot & \cdot & & & \end{bmatrix}$$

$$\begin{bmatrix} \lambda_1 & & & & \\ & \lambda_2 & & & \\ & & \cdot & & \\ & & & \cdot & \\ & & & & \cdot \end{bmatrix} \begin{bmatrix} \cdot & \cdot & \ell_1 & \cdot & \cdot \\ \cdot & \cdot & \ell_2 & \cdot & \cdot \\ & & \cdot & & \\ & & \cdot & & \\ & & \cdot & & \end{bmatrix}$$

Now introduce the complex matrices

$$J = \frac{1}{\sqrt{2}} \begin{bmatrix} 1 & 1 & & & \\ i & -i & & & \\ & & \sqrt{2} & & \\ & & & \cdot & \\ & & & & \cdot \end{bmatrix},$$

$$J^T = \frac{1}{\sqrt{2}} \begin{bmatrix} 1 & i & & & \\ 1 & -i & & & \\ & & \sqrt{2} & & \\ & & & \cdot & \\ & & & & \cdot \end{bmatrix}$$

and rewrite the factorization

$$A^{-1}B = (RJ^T)((J^T)^{-1}\Lambda J^{-1})(JL) = R^{\#}\Lambda^{\#}L^{\#}$$

Then it can be verified that $R^{\#}, L^{\#}$ are real matrices, and that $\Lambda^{\#}$ is the real symmetric matrix

$$\Lambda^{\#} = (J^T)^{-1}\Lambda J^{-1} = \begin{bmatrix} \lambda_R & \lambda_I & & & \\ \lambda_I & -\lambda_R & & & \\ & & \lambda_3 & & \\ & & & \cdot & \\ & & & & \cdot \end{bmatrix}$$

Now we write the governing equations in the form (15.2) with $S = (R^{\#})^{-1}A^{-1}$ and $Q = (L^{\#})^{-1}$; the result, after partial simplification, is

$$(R^{\#})^{-1}(L^{\#})^{-1}\partial_x v + \Lambda^{\#}\partial_y v = 0$$

Here,

$$\begin{aligned} (R^{\#})^{-1}(L^{\#})^{-1} &= (L^{\#}R^{\#})^{-1} \\ &= (JLRJ^T)^{-1} \\ &= (JJ^T)^{-1} \\ &= \begin{bmatrix} 1 & 0 & & & \\ 0 & -1 & & & \\ & & 1 & & \\ & & & \cdot & \\ & & & & \cdot \end{bmatrix}. \end{aligned}$$

Thus, when expressed in terms of variables $\mathbf{v} = L^{\#}\mathbf{u}$, the equations decouple into $(m-2)$ advection equations, and the 2×2 symmetric elliptic system

$$\begin{pmatrix} 1 & 0 \\ 0 & -1 \end{pmatrix} \partial_x \begin{pmatrix} u \\ v \end{pmatrix} +$$

$$\begin{pmatrix} \lambda_R & \lambda_I \\ \lambda_I & -\lambda_R \end{pmatrix} \partial_y \begin{pmatrix} u \\ v \end{pmatrix} = 0. \qquad (15.3)$$

If there is more than one conjugate pair of eigenvalues, the treatment above can easily be extended by adding additional (2×2) blocks to the matrix J, so we have

<u>THEOREM</u> Any $(m \times m)$ first order constant coefficient hyperbolic system in two dimensions decomposes into $(m - 2k)$ convection equations and k independent (2×2) symmetric elliptic systems.

<u>REMARK</u> The $(m \times 2)$ blocks that appear in $R^{\#}$ provide basis vectors for the subspaces inhabited by the elliptic subproblems; the $(2 \times m)$ blocks that appear in $L^{\#}$ are operators that project an arbitrary vector into these subspaces.

15.2 Steady Euler Equations

Take the vector of unknowns to be $d\mathbf{u} = (\frac{dp}{\rho c}, du, dv, dp - c^2 d\rho)^T$, and adopt coordinates aligned with the flow direction. Then A, B are the symmetric matrices

$$A = \begin{bmatrix} M & 1 & 0 & 0 \\ 1 & M & 0 & 0 \\ 0 & 0 & M & 0 \\ 0 & 0 & 0 & M \end{bmatrix}, B = \begin{bmatrix} 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 \\ 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \end{bmatrix}$$

We then find that the equation $A^{-1}B = R\Lambda L$ becomes

$$A^{-1}B = \begin{bmatrix} 0 & 0 & \frac{M}{M^2-1} & 0 \\ 0 & 0 & \frac{-1}{M^2-1} & 0 \\ \frac{1}{M} & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \end{bmatrix} =$$

$$\begin{bmatrix} M & M & 0 & 0 \\ -1 & -1 & 1 & 0 \\ \sqrt{M^2-1} & -\sqrt{M^2-1} & 0 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

$$\begin{bmatrix} \frac{1}{\sqrt{M^2-1}} & 0 & 0 & 0 \\ 0 & \frac{-1}{\sqrt{M^2-1}} & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \end{bmatrix}$$

$$\begin{bmatrix} \frac{1}{2M} & 0 & \frac{1}{2\sqrt{M^2-1}} & 0 \\ \frac{1}{2M} & 0 & \frac{-1}{2\sqrt{M^2-1}} & 0 \\ \frac{1}{M} & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

For supersonic flow, the transformation $\mathbf{v} = L\mathbf{u}$ produces four real characteristic equations, which are, in primitive variables,

$$\begin{aligned} \partial_x S &= 0 \quad dS = dp - a^2 d\rho \\ \partial_x H &= 0 \quad dH = dp + \frac{\rho}{2}(u^2) \\ (\beta\partial_x + \partial_y)(\beta dp + \rho u dv) &= 0 \\ (\beta\partial_x - \partial_y)(\beta dp - \rho u dv) &= 0 \end{aligned}$$

where $\beta^2 = M^2 - 1$.

If $M^2 < 1$, two of these characteristic equations break down. We may then have recourse to the alternative factorization $R^{\#}\Lambda^{\#}L^{\#}$, which is

$$A^{-1}B = \begin{bmatrix} 0 & 0 & \frac{M}{M^2-1} & 0 \\ 0 & 0 & -\frac{1}{M^2-1} & 0 \\ \frac{1}{M} & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \end{bmatrix}$$

$$= \begin{bmatrix} \sqrt{2}M & 0 & 0 & 0 \\ -\sqrt{2} & 0 & 1 & 0 \\ 0 & -\sqrt{2(1-M^2)} & 0 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

$$\begin{bmatrix} 0 & \frac{-1}{\sqrt{1-M^2}} & 0 & 0 \\ \frac{-1}{\sqrt{1-M^2}} & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \end{bmatrix}$$

$$\begin{bmatrix} \frac{1}{\sqrt{2}M} & 0 & 0 & 0 \\ 0 & 0 & \frac{1}{\sqrt{2(1-M^2)}} & 0 \\ \frac{1}{M} & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

From this factorization we recover the same streamwise characteristic equations as in the supersonic case. It is interesting to note that the entropy characteristic corresponds to a shared eigenvector of the matrices A, B, whereas the enthalpy characteristic does not. The two acoustic characteristics collapse into the elliptic system deriving from (15.3), which is

$$\begin{pmatrix} 1 & 0 \\ 0 & -1 \end{pmatrix} \partial_x \begin{pmatrix} \frac{\beta_*}{\rho u} dp \\ dv \end{pmatrix}$$

$$+ \begin{pmatrix} 0 & \frac{-1}{\beta_*} \\ \frac{-1}{\beta_*} & 0 \end{pmatrix} \partial_y \begin{pmatrix} \frac{\beta_*}{\rho u} dp \\ dv \end{pmatrix} = 0. \qquad (15.4)$$

where $\beta_*^2 = 1 - M^2$.

These are the Cauchy-Riemann equations written in Prandtl-Glauert coordinates $(x, y/\beta_*)$. Hence, we can express this as two scalar second order elliptic equations.

This decomposition differs from that found by Ta'asan He employed, as canonical variables, (S, H, u, v) and his decomposition was not completely block diagonal, containing some additional coupling terms. The variables which emerge from the present treatment are (S, H, p, v) and there is no coupling between blocks.

15.3 Preconditioning

Suppose that the time-dependent two-dimensional problem obeys

$$\partial_t u + A\partial_x u + B\partial_y u = 0 \qquad (15.5)$$

where A and B are symmetric. To find a decomposition of this equation as it stands would require a three-dimensional treatment. However, there are occasions when only the steady state is of interest, but it is convenient to compute it by following some time-like evolution. In such cases (15.5) may be replaced (sometimes advantageously [25, 26, 30]) by

$$\mathbf{P}^{-1}\partial_t u + A\partial_x u + B\partial_y u = 0 \qquad (15.6)$$

where P is a 'preconditioning matrix'. To retain well-posedness, P must be positive definite. In this section we point out that P can always be chosen to preserve the canonical block-diagonal form of the steady state equations.

As in the steady case, premultiply (15.6) by $(R^{\#})^{-1}A^{-1}$ and make the change of variable $\mathbf{v} = L^{\#}\mathbf{u}$; this gives

$$(R^{\#})^{-1}A^{-1}\mathbf{P}^{-1}(L^{\#})^{-1}\partial_t v \\ + (JJ^T)^{-1}\partial_x v + \Lambda^{\#}\partial_y v = 0.$$

For the decomposition to be preserved, it is necessary and sufficient that

$$(R^{\#})^{-1}A^{-1}\mathbf{P}^{-1}(L^{\#})^{-1} = D^{\#}$$

where $D^{\#}$ is block diagonal of the same form as the matrices that multiply the space derivatives. Solving for $\mathbf{P}$ gives

$$\mathbf{P} = (R^{\#}ADL^{\#})^{-1}.$$

where the only constraint on $D^{\#}$ is that it shall be positive definite to ensure well-posedness.

To apply this analysis to the Euler equations we take

$$D^{\#} = \begin{pmatrix} P & Q & 0 & 0 \\ R & S & 0 & 0 \\ 0 & 0 & \frac{1}{M} & 0 \\ 0 & 0 & 0 & \frac{1}{M} \end{pmatrix}.$$

This assigns the fluid velocity u to each of the scalar waves. We require $\Delta = PS - QR > 0$ for positive definiteness. After carrying through the required operations we find that

$$\mathbf{P}^{-1} = \begin{pmatrix} \frac{1}{M^2} - P\frac{\beta_*^2}{M} & \frac{1}{M} & Q\beta_* & 0 \\ \frac{1}{M} & 1 & 0 & 0 \\ R\beta_* & 0 & -SM & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}.$$

and also

$$\mathbf{P} = \begin{pmatrix} -\frac{S}{\Delta}\frac{M}{\beta_*^2} & \frac{S}{\Delta}\frac{1}{\beta_*^2} & -\frac{Q}{\Delta}\frac{1}{\beta_*} & 0 \\ \frac{S}{\Delta}\frac{1}{\beta_*^2} & 1-\frac{S}{\Delta}\frac{1}{M\beta_*^2} & \frac{Q}{\Delta}\frac{1}{M\beta_*} & 0 \\ -\frac{R}{\Delta}\frac{1}{\beta_*} & \frac{R}{\Delta}\frac{1}{M\beta_*} & -\frac{P}{\Delta}\frac{1}{M} & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}.$$

This is the most general preconditioner that preserves the canonical decomposition. It may be noted that $\det P = (\beta_*^2\Delta)^{-1}$. The preconditioner of van Leer *et. al.* [30] corresponds to the special case $P = S = -1/(M\beta_*)$, $Q = R = 0$, $\Delta = 1/(M^2\beta_*^2)$.

It is still an open question which choice of $\mathbf{P}$ leads to the fastest and most robust convergence to a steady state for a numerical code. This is principally because it is not easy to translate these qualities into mathematical terms. Here, we will identify robustness with the behavior of the solutions as $M \to 0$. We identify the rate of convergence with the condition number i.e. the ratio of the largest and smallest propagation speeds in the transient solution. We wish this condition number to be chosen as small as possible. [1] We will also insist on symmetry requirements for well-posedness.

When the preconditioned equations are written in Cartesian coordinates not aligned with the flow, terms may appear which depend on the flow direction as the flow velocity vanishes. A necessary and sufficient condition to avoid this phenomenon is that $P_{22} = P_{33}$, which implies

$$\beta_*^2(M\Delta + P) = S. \qquad (15.7)$$

The wavespeeds in the direction θ are given by

$$\det[A\cos\theta + B\sin\theta - P^{-1}\lambda]$$

which gives a twice repeated root $\lambda = M\cos\theta$, together with the quadratic term

$$\Delta\beta^2\lambda^2 + [(P-S)\beta^2\cos\theta + (Q+R)\beta\sin\theta]\lambda \\ = \beta^2\cos^2\theta + \sin^2\theta.$$

To keep this symmetrical with respect to the streamline, we must take $Q + R = 0$, and we consider first the case $Q = R = 0 \Rightarrow \Delta = AD$. The wavespeeds in the x-direction are then $1/P$ and $-1/S$, and in the y-direction $/pm1/(\beta_*\sqrt{PS})$. It can be shown that the best condition number is obtained from the preconditioner of van Leer *et. al.*, but unfortunately this does not satisfy the condition (15.7) at low Mach numbers. We require, in fact, that as $M \to 0$, then

$$(S + 1/M)(P - 1/M) = -1/M^2.$$

This is the graph of a hyperbola in the SP plane. We are only concerned with the branch that passes through the origin (the other branch leads to imaginary wavespeeds), and only with the half of that branch for which P, S are both negative (the other half does not make P positive definite). The condition number based solely on the 'acoustic' waves is

$$K = \max(S/P, P/S)$$

[1] In practice life is not this simple. Choosing different preconditioners also changes the "artificial" viscosity associated with the scheme which in turn affects the rate of convergence. Hence, in applications it is not always the lowest condition number that gives the quickest convergence [27, 28].

which is unity at the origin and degrades away from it. Taking into account that the flow velocity is M, and that $|P| > |S|$,we actually have

$$K = \max\left(\frac{S}{P}, \frac{P}{S}, \frac{1}{MS}, MP\right).$$

The point on the hyperbola that minimizes this is

$$P = \frac{-1}{M} \quad S = \frac{-1}{2M}$$

leading to K=2.

Of course, the preconditioner does not have to satisfy (15.7) away from $M = 0$, and can be blended in with the van Leer *et.al.* preconditioner, by some such choice as

$$P = \frac{-1}{M\beta_*},\ S = \frac{-1}{M * \beta_*(1+\beta_*)}$$

which leads to the simple preconditioner

$$\mathbf{P} = \begin{pmatrix} \frac{M^2}{\beta_*} & \frac{-M}{\beta_*} & 0 & 0 \\ \frac{-M}{\beta_*} & \frac{1+\beta_*}{\beta_*} & 0 & 0 \\ 0 & 0 & \beta_*(1+\beta_*) & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix},$$

$$\mathbf{P}^{-1} = \begin{pmatrix} \frac{1+\beta_*}{M^2} & \frac{1}{M} & 0 & 0 \\ \frac{1}{M} & 1 & 0 & 0 \\ 0 & 0 & \frac{1}{\beta_*(1+\beta_*)} & 0 \\ 0 & 0 & 0 & 1 \end{pmatrix}.$$

Rather strikingly, these are identical with those given by van Leer *et.al.*, except for the factors $(1 + \beta_*)$ in the $()_{33}$ elements. Further details can be found in [19].

16 Three Dimensions

16.1 General Steady-state Problems

The most common block diagonal forms in three-dimensional problems appear to have blocks that are either scalar or else (3×3). The possibility of (2×2) blocks is ruled out, apart from exceptional cases, by an anlysis of Gilquin, Laurens and Rosier [8], who considered the general (2×2) symmetric system in multi-dimensions. They only require that the system be strongly hyperbolic (i.e. combinations of the coefficient matrices can always be diagonalized). They then prove that such systems can always be decomposed into a convective part (possibly with speed zero) and a *two dimensional* elliptic part. Therefore, (2×2) blocks are incapable of representing three-dimensional elliptic systems.

Due to the complexity of the general three dimensional case we shall only consider the special case of the linearized Euler equations.

16.2 Subsonic

We consider the preconditioned subsonic equations for three dimensions in streamwise coordinates. We shall analyze the specific preconditioning suggested by van Leer, Lee and Roe [30]. By our previous discussion the decomposition also applies to the steady state equations without any preconditioning. Let $\beta_* = \sqrt{1-M^2}$.

$$\begin{aligned} \frac{\beta_*+1}{M^2}p_t + \frac{\rho u}{M^2}u_t + up_x + \rho c^2(u_x+v_y+w_z) &= 0 \\ \frac{1}{\rho u}p_t + u_t + uu_x + \frac{p_x}{\rho} &= 0 \\ \frac{1}{\beta_*}v_t + uv_x + \frac{p_y}{\rho} &= 0 \\ \frac{1}{\beta_*}w_t + uw_x + \frac{p_z}{\rho} &= 0 \\ S_t + uS_x &= 0 \end{aligned}$$

S and H are convected along the stream line. We now have three equations for the unknowns (p,v,w). Let $(dq, dr, ds) = (\frac{\beta_*}{\rho u}dp, du, dv)$.

$$\begin{pmatrix} q \\ r \\ s \end{pmatrix}_t + \begin{pmatrix} -\beta_* u & 0 & 0 \\ 0 & \beta_* u & 0 \\ 0 & 0 & \beta_* u \end{pmatrix} \begin{pmatrix} q \\ r \\ s \end{pmatrix}_x +$$

$$\begin{pmatrix} 0 & u & 0 \\ u & 0 & 0 \\ 0 & 0 & 0 \end{pmatrix} \begin{pmatrix} q \\ r \\ s \end{pmatrix}_y + \begin{pmatrix} 0 & 0 & u \\ 0 & 0 & 0 \\ u & 0 & 0 \end{pmatrix} \begin{pmatrix} q \\ r \\ s \end{pmatrix}_z = 0$$

We next rescale x by defining $x = \beta_* x'$. We rewrite this equation in terms of x' and then drop the prime. The effect is to eliminate the β_* term from the x derivative. Then in this modified coordinate system we get

$$\begin{pmatrix} q \\ r \\ s \end{pmatrix}_t + \begin{pmatrix} -u & 0 & 0 \\ 0 & u & 0 \\ 0 & 0 & u \end{pmatrix} + \begin{pmatrix} q \\ r \\ s \end{pmatrix}_x + \quad (16.1)$$

$$\begin{pmatrix} 0 & u & 0 \\ u & 0 & 0 \\ 0 & 0 & 0 \end{pmatrix} \begin{pmatrix} q \\ r \\ s \end{pmatrix}_y + \begin{pmatrix} 0 & 0 & u \\ 0 & 0 & 0 \\ u & 0 & 0 \end{pmatrix} \begin{pmatrix} q \\ r \\ s \end{pmatrix}_z = 0$$

We wish to know when this first order system is equivalent to the Laplace equation. To do this we study the equivalence of the three dimensional Laplace equation with a first order system. Let

$$\frac{\partial^2\psi}{\partial x^2} + \frac{\partial^2\psi}{\partial y^2} + \frac{\partial^2\psi}{\partial z^2} = 0.$$

Define $u = \psi_x$, $v = -\psi_y$ and $w = -\psi_z$. Then

$$\begin{pmatrix} -1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{pmatrix} \begin{pmatrix} u \\ v \\ w \end{pmatrix}_x + \begin{pmatrix} 0 & 1 & 0 \\ 1 & 0 & 0 \\ 0 & 0 & 0 \end{pmatrix} \begin{pmatrix} u \\ v \\ w \end{pmatrix}_y$$

$$+ \begin{pmatrix} 0 & 0 & 1 \\ 0 & 0 & 0 \\ 1 & 0 & 0 \end{pmatrix} \begin{pmatrix} u \\ v \\ w \end{pmatrix}_z = 0.$$

Hence, it is trivial that the second order three dimensional Laplace equation yields the first order system. However, one can not, in general, start with the (u, v, w) first order system and obtain a Laplace equation for each of the variables. By the existence of the potential ψ we also have $v_z - w_y = 0$. If this is added as an additional equation to the system then it is easily shown that (u, v, w) do satisfy a Laplace equation for each variable. Hence, to go from the system back to the second order Laplace equation for a potential ψ we have a compatibility requirement on the solution.

For the three dimensional Euler equations the "acoustic" portion corresponds to the Laplace equation (or time dependent wave equation) only if we satisfy a compatibilty constraint corresponding to the vanishing of the streamwise component of the vorticity. If this constraint is not met then we can only diagonalize the system by including higher derivatives.

Starting with (16.1) and differentiating we find that q satisfies the wave equation $\frac{\partial^2 q}{\partial t^2} = u^2 \Delta q$. However r and s do not obey a wave equation. Instead

$$\begin{aligned} \frac{\partial^2 r}{\partial t^2} &= u^2 (\frac{\partial^2 r}{\partial x^2} + \frac{\partial^2 r}{\partial y^2} + \frac{\partial^2 s}{\partial y \partial z}) \\ &= u^2 \left(\Delta r + \frac{\partial}{\partial z} (\frac{\partial s}{\partial y} - \frac{\partial r}{\partial z}) \right) \\ \frac{\partial^2 s}{\partial t^2} &= u^2 (\frac{\partial^2 s}{\partial x^2} + \frac{\partial^2 s}{\partial z^2} + \frac{\partial^2 r}{\partial y \partial z}) \\ &= u^2 \left(\Delta s - \frac{\partial}{\partial y} (\frac{\partial s}{\partial y} - \frac{\partial r}{\partial z}) \right) \end{aligned}$$

Differentiate the equation for r by y and the equation for s by z and add we find that $\frac{\partial^2 (r_y + s_z)}{\partial t^2} = u^2 \Delta (r_y + s_z)$, i.e.$(r_y + s_z)$ also satisfies the wave equation. Since q satisfies a wave equation so does q_x and hence so does the divergence $q_x + r_y + s_z$. Define $\omega = r_z - s_y$ i.e. the z component of the vorticity. Differentiating the equation for r by z and the equation for s by y and subtracting we find that $\omega_t + u\omega_x = 0$. Thus, we have two "elliptic" variables, q and div(q,r,s) and one "hyperbolic" variable ω in addition to the previous two hyperbolic variables S and H. Hence, if we solve this three dimensional system with an initial condition that the vorticity is zero then the vorticity remains zero for all time. In this case we can go from the first order system back to the second order wave equation. In two dimensions the system is purely elliptic since ω is always identically zero.

16.3 Supersonic

In three dimensions we consider the van Leer et. al. preconditioned supersonic equations in streamwise coordinates. As before this also applies to the non-preconditioned steady state equations. Let $\beta = \sqrt{M^2 - 1}$.

$$\begin{aligned} \frac{\beta M + 1}{M^2} p_t + \frac{\rho c}{M} u_t + u p_x + \rho c^2 (u_x + v_y + w_z) &= 0 \\ \frac{1}{\rho u} p_t + u_t + u u_x + \frac{p_x}{\rho} &= 0 \\ \frac{M}{\beta} v_t + u v_x + \frac{p_y}{\rho} &= 0 \\ \frac{M}{\beta} w_t + u w_x + \frac{p_z}{\rho} &= 0 \\ S_t + u S_x &= 0 \end{aligned}$$

Solving for (p, u, v, w, S) we get

$$\begin{aligned} p_t + \frac{\beta u}{M} p_x + \frac{\rho c^2 M}{\beta} (v_y + w_z) = 0 \\ u_t + u u_x - \frac{1}{\rho} \left(\frac{\beta}{M} - 1 \right) p_x - \frac{c}{\beta} (v_y + w_z) = 0 \\ v_t + \frac{\beta}{M} (u v_x + \frac{p_y}{\rho}) = 0 \\ w_t + \frac{\beta}{M} (u w_x + \frac{p_z}{\rho}) = 0 \\ S_t + u S_x = 0 \end{aligned}$$

As before the system for (p,v,w) decouples from the rest. Let $\mathbf{w} = (\frac{\beta}{\rho u} dp, dvdw)^t$. Then

$$\mathbf{w}_t + \frac{\beta u}{M} \begin{pmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{pmatrix} \mathbf{w}_x \qquad (16.2)$$

$$+ \begin{pmatrix} 0 & c & 0 \\ c & 0 & 0 \\ 0 & 0 & 0 \end{pmatrix} \mathbf{w}_y + \begin{pmatrix} 0 & 0 & c \\ 0 & 0 & 0 \\ c & 0 & 0 \end{pmatrix} \mathbf{w}_z = 0$$

Normalizing (16.2) we have

$$\mathbf{w}_t + \mathbf{w}_x + B\mathbf{w}_y + C\mathbf{w}_z = 0$$

with

$$B = \begin{pmatrix} 0 & 1 & 0 \\ 1 & 0 & 0 \\ 0 & 0 & 0 \end{pmatrix} \qquad C = \begin{pmatrix} 0 & 0 & 1 \\ 0 & 0 & 0 \\ 1 & 0 & 0 \end{pmatrix}$$

This is a new canonical form which cannot be reduced to either a hyperbolic (convective) equation or to an elliptic (acoustic) equation. Instead since the coefficient matrix for the x direction reduces to the identity matrix we can introduce new variables $\tau = t$ and $\xi = x - t$. Then

$$\mathbf{w}_\tau + B\mathbf{w}_y + C\mathbf{w}_z = 0 \qquad \mathbf{w} = (q, r, s)^t$$

This is identical to the canonical form for the subsonic case considered above. Hence, q satisfies a wave equation and r, s satisfy

$$\begin{aligned} \frac{\partial^2 r}{\partial t^2} &= \Delta r + \frac{\partial}{\partial z}(\frac{\partial s}{\partial y} - \frac{\partial r}{\partial z}) \\ \frac{\partial^2 s}{\partial t^2} &= \Delta s - \frac{\partial}{\partial y}(\frac{\partial s}{\partial y} - \frac{\partial r}{\partial z}) \end{aligned}$$

So, $r_y + s_z$ satisfies a two dimensional wave equation while $(s_y - r_x)_\tau = 0$ in the moving coordinate system. Hence, the vorticity component $s_y - r_x$ satisfies a one dimensional convection equation, in the steamwise direction, as we already have found.

Thus, the supersonic system consists of three convective equations for the entropy, enthalpy and vorticity that decouple. In addition we have a system of two equations that is a combined hyperbolic-elliptic system in the sense that it is an elliptic system in the y and z directions in a system moving in the x direction.

17 Comparison of Preconditioners

- Turkel and Van Leer preconditioners
  - For low speed flow: convergence and accuracy
    Gives large time step for low Mach numbers
  - Based on *PDE* i.e. low frequencies
  - Changes steady state solution
- Allmaras - Giles preconditioner

$$\begin{aligned}(|A| + |B|)w_t = \\ Aw_x + Bw_y + h(|A|w_{xx} + |B|w_{yy})\end{aligned}$$

  - Works on high frequencies (high-high vs high-low)
  - Depends on individual scheme
  - At (π, π) converts matrix function to scalar
  - Does not change steady state solution
  - Does not give any benefit for low Mach numbers
  - Requires small time step - no residual smoothing allowed
  - Requires inversion of matrix (2D/3D)

Preconditioning-squared

Combine Turkel/van-Leer with Jacobi

$$\begin{aligned}(|PA| + |PB|)w_t = \\ PAw_x + PBw_y + h(|PA|w_{xx} + |PB|w_{yy})\end{aligned}$$

18 Computational Results

18.1 Inviscid Flow

To assess the accuracy of the preconditioning versus the standard algorithm we compare the results for lift and drag for inviscid flow over NACA 0012 airfoil. The C-type grid has 224 $\times$ 40 cells clustered near the leading and trailing edges in order to allow accurate drag computations, for various Mach numbers, with the results from a panel method. As seen in table 1 the code using the preconditioning (both $\alpha = 0$ and $\alpha = 1$) gives lift and drag quite close to the panel method results with only a small dependence on the Mach number. The non-preconditioned code has large variations as the Mach number goes to zero and is not converging to the panel code results. In particular the drag, which should be zero for inviscid flow, is very large without preconditioning but close to zero when using preconditioning. In Figure 1 we compare the C_p for this case without and without the preconditioning. Other comparisons with incompressible solutions are presented in [29].

	Mach	panel	no prec	α=0	α=1
C_L	0.1	.241	.2448	.2434	.2429
	0.01		.2172	.2421	.2416
	0.001		.1097	.2421	.2416
C_D	0.1	0.0	.0008	.00027	.00023
	0.01		.0086	.00027	.00023
	0.001		.0731	.00027	.00023

Table 1: Comparison of lift and drag with/without preconditioning

Figure 1: Comparison of C_p with and without preconditioning, $M_\infty = 0.01$

Figure 2a: Partial view of block-structured grid for 3-element high lift airfoil configuration

18.2 2-D Multi-element Airfoil

The 3-element airfoil configuration has been investigated both experimentally and theoretically [35]. Present computations are performed at a chord Reynolds number of 9 million and an angle of attack of 16.2 degrees using a variant of a cell-centered code [28]. The Mach number for this case is 0.2. A 20-block structured grid shown in Figure 2a, is used for the computations. This case has also been investigated with the original non-preconditioned version of the flow solver used in this work [32].

The convergence histories for this case are presented in Figure 2b, where the results from original non-preconditioned and current preconditioned (conservative) schemes are compared. The residual in the original code slow down considerably at approximately 4 orders; while the residual in the preconditioned scheme exhibits much better convergence. Note that the free-stream Mach number for this case (M=0.2) is generally not considered too low for compressible codes. However, several pockets of slow-moving flow exist in the cove regions of the slat and the main airfoil sections [32]. These pockets slow the convergence of standard compressible codes.

The computed pressure distributions for this case are compared in Figure 2c. As expected, very little difference is observed in the two sets of computed results. Furthermore these results compare quite favorably with the experimental data. Further results are presented in [28].

Figure 2b: Effect of preconditioning on convergence history for the the 3-element high-lift airfoil configuration

Figure 2c: Effect of preconditioning on pressure distributions for the 3-element high-lift airfoil configuration

18.3 Flow over 3D Wing

The three-dimensional calculations have been carried out with a cell-vertex method [15] which corresponds closely to *Code1* used for the 2D flows. The code uses central differencing with artificial viscosity, multistage time stepping with a five stage scheme, residual smoothing and a 3 level full multigrid with W-cycles. Preconditioning is obtained using $\delta = 1, \alpha = 0$ and the dissipation according to (7.3).

We consider essentially incompressible viscous flow over an ONERA-M6 wing at an angle of attack of $\alpha = 2°$, Re=11 million. The effect of turbulence is modelled by the Baldwin and Lomax model. The grid used for the calculations has C-H topology and consists of 224 cells in the streamwise direction, 48 cells normal and 32 cells in the spanwise directions. Figure 3 shows the grid in the plane of symmetry. The residual convergence for computations at $M_\infty = 0.10, 0.01, 0.001$ is presented in Figure 4a. It is seen that the rate of convergence is independent of the free stream Mach number. Without preconditioning no convergence could be obtained for Mach numbers less than 0.1. Figure 4b compares the surface pressure distribution at spanwise section $\eta = 0.8$. There is no effect of the freestream Mach number visible. Mach number independence is further confirmed by Figure 4c where the total lift and pressure drag coefficients are plotted versus the Mach number. These values are constant if the Mach number approaches zero.

Figure 3: Wing surface and grid in symmetry plane

Figure 4a: Effect of freestream Mach number on residual convergence of 3D wing

Figure 4b: Effect of freestream Mach number on pressure distribution of 3D wing

Figure 4c: Effect of freestream Mach number on force coefficients of 3D wing

References

[1] Allmaras, S. *Analysis of a Local Matrix Preconditioner for the 2-D Navier-Stokes Equations*, AIAA 11th Computational Fluid Dynamics Conference, 1995.

[2] Allmaras, S. *Analysis of Semi-Implicit Preconditioners for Multigrid Solution of the 2-D Compressible Navier-Stokes Equations*, AIAA paper 95-1651-CP, AIAA 12th Computational Fluid Dynamics Conference, 1995.

[3] Arnone A. and Turkel E. *Pseudo-compressibilty Methods for the Incompressible Flow Equations*, Proceedings 11th AIAA CFD Conference, pp. 349-357, AIAA paper 93-3329, 1993.

[4] Au-Yeung, Y.H. Proceedings Amer. Math. Soc., 20:545-548, 1969.

[5] Choi, Y.-H. and Merkle, C.L. *The Application of Preconditioning to Viscous Flows*, J. Comput. Phys., 105:207-223, 1993.

[6] Chorin, A.J. *A Numerical Method for Solving Incompressible Viscous Flow Problems*, J. Comput. Phys., 2:12-26, 1967.

[7] Fiterman, A., Turkel, E. and Vatsa, V. *Pressure Updating Methods for the Steady-State Fluid Equations*, AIAA 95-1652-CP, AIAA 12th Computational Fluid Dynamics Conference, 1995.

[8] Gilquin, H., Laurens, J. and Rosier, C. *Multi-Dimensional Riemann Problems for Linear Hyperbolic Systems: Part I* in Nonlinear Hyperbolic Problems: Theoretical, Applied and Computational Aspects, eds A. Donato and F. Oliveri, pp. 276-279 Vieweg, 1993

[9] Gustafsson, B. *Unsymmetric Hyperbolic Systems and the Euler equations at Low Mach Numbers*, J. Scientific Computing, 2:123-136, 1987.

[10] Gustafsson, B. and Stoor, H. *Navier-Stokes Equations for Almost Incompressible Flow*, SIAM J. Numer. Anal., 28:1523-1547, 1991.

[11] Jameson, A., Schmidt, W. and Turkel, E. *Numerical Solutions of the Euler Equations by a Finite Volume Method using Runge-Kutta Time-Stepping Schemes*, AIAA paper 81-1259, 1981.

[12] Klainerman, S. and Majda, A. *Compressible and Incompressible Fluids*, Comm. Pure Appl. Math., 35:629-651, 1982.

[13] Kreiss, H.O. and Lorenz, J. **Initial-Boundary Value Problems and the Navier Stokes Equations**, Academic Press, Boston, 1989.

[14] Kreiss, H.O., Lorenz,J. and Naughton, M. *Convergence of the Solutions of the Compressible to the Solutions of the Incompressible Navier-Stokes Equations*, Advances in Appl. Math., 12:187-214, 1991.

[15] Kroll, N., Radespiel, R. and Rossow, C.-C. *Accurate and Efficient Flow Solvers for 3D Applications on Structured Meshes*, VKI Lecture Series, LS-04, 1994.

[16] Lee, D. and Van Leer, B. *Progress in Local Preconditioning of the Euler and Navier-Stokes Equations*, AIAA 11th Computational Fluid Dynamics Conference, pp. 338-348, 1993.

[17] Mesaros, L. and Roe, P. *Multidimensional Fluctuation Splitting Schemes Based on Decomposition Methods*, AIAA 12th Computational Fluid Dynamics Conference, pp. 582-591, 1995.

[18] Pierce, N.A. and Giles, M.B. *Preconditioning Compressible Flow Calculations on Stretched Meshes* AIAA paper 96-0889, 1996.

[19] Roe, P. and Turkel, E. *The Quest for Diagonalization of Differential Systems*, Workshop on Barriers and Challenges in Computational Fluid Dynamics, Kluwer Publisher, 1996.

[20] Swanson, R.C. and Radespiel, R. *Cell Centered and Cell Vertex Multigrid Schemes for the Navier-Stokes Equations*, AIAA J., 29:697-703, 1991.

[21] Swanson, R.C. and Turkel, E. *Artificial Dissipation and Central Difference Schemes for the Euler and Navier-Stokes Equations*, AIAA paper 87-1107-CP, AIAA 8th Computational Fluid Dynamics Conference, 1987.

[22] Swanson, R.C. and Turkel, E. *On Central Difference and Upwind Schemes*,J. Comput. Phys., 101:292-306, 1992

[23] Ta'asan, S. *Canonical-Variables Multigrid Method for Steady-State Euler Equations. Fourteenth Inter. Conf. Numer. Meth. Fluid Dynamics*, Lecture Notes in Physics, Editor Deshpande et. al, Springer 1994.

[24] Ta'asan, S. *Essentially Optimal Multigrid Method for Steady State Euler Equations* AIAA Paper 95-0209, 1995.

[25] Turkel, E. *Preconditioned Methods for Solving the Incompressible and Low Speed Compressible Equations*, J. Comput. Phys., 72:277-298, 1987.

[26] Turkel, E. *A Review of Preconditioning Methods for Fluid Dynamics*, Applied Numerical Mathematics, 12:257-284, 1993.

[27] Turkel, E., Fiterman, A. and van Leer, B. *Preconditioning and the Limit to the Incompressible Flow Equations*, Computing the Future: **Frontiers of Computational Fluid Dynamics 1994**, editors D.A. Caughey and M.M. Hafez, Wiley Publishing, 215-234, 1994.

[28] Turkel, E., Vatsa, V.N. and Radespiel, R. *Preconditioning Methods for Low Speed Flow*, AIAA paper 96-2460, 1996.

[29] Turkel, E., Radespiel, R. and Kroll, N. *Assessment of Two Preconditioning Methods for Aerodynamic Problems* to appear Computers and Fluids.

[30] van Leer, B., Lee, W.T., Roe, P.L. *Characteristic Time-Stepping or Local Preconditioning of the Euler Equations*, AIAA Paper 91-1552, 1991.

[31] van Leer, B., Mesaros, L., Tai, C-H and Turkel, E. *Local Preconditioning in a Stagnation Point*, AIAA paper 95-1654-CP, AIAA 12th Computational Fluid Dynamics Conference, 88-101, 1995.

[32] Vatsa, V.N., Sanetrik, M.D., Parlette, E.B., Eiseman, P. and Cheng, Z. Multi-block Structured Grid Approach for Solving Flows over Complex Aerodynamic Configurations, AIAA Paper 94-0655, 1994.

[33] Volpe, G. *Performance of Compressible Flow Codes at Low Mach Numbers*, AIAA J., 31:49-56, 1993.

[34] Wen-Tzong Lee **Local preconditioning of the Euler equations**, Ph.D. dissertation, The University of Michigan, 1992.

[35] Workshop on high-lift flow physics for application to subsonic aircraft. Workshop held at NASA Langley Research Center, May 18-20, 1993.